

Tubosa track light adjustable H150/55 GU10 matte black



Tubosa track light adjustable H150/55 GU10 matte black	
ARTICLE_NUMBER:	590074.00A
CHANGED_LAST:	16-09-2025
BRAND:	Daylight Italia
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001744 - Downlight/spot/floodlight
SYNONYM:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight



FEATURES

Protection class according to IEC 61140:	--	Built-in width:	NA mm
Width:	-mm	Colour consistency (McAdam ellipse):	NA mm
Outer diameter:	-mm	Total harmonic distortion:	NA mm
Reflector:	-mm	Photobiological safety according to EN 62471:	NA mm
Lamp holder:	-mm	Degree of protection (NEMA):	NA mm
Conductor cross section:	-mm ²	Rated ambient temperature according to IEC 62722-2-1:	NA °C
Connection type:	-mm ²	Filament test according to IEC 60695-2-11:	NA °C
Housing colour:	-mm ²	Dimming 0-10 V:	NO
Dimmable:	NO	Dimming 1-10 V:	NO
Surface protection:	NO	Dimming DALI:	NO
Voltage type:	NO	Dimming DMX:	NO
With movement sensor:	NO	Dimming potentiometer (integrated):	NO
Suitable for lamp power:	NA W	Dimming LineSwitch:	NO
Type of control gear:	NA W	Dimming manufacturer's proprietary system:	NO
Colour rendering index CRI:	NA W	Dimming mains voltage modulation:	NO
Suitable for wall mounting:	NO	Dimming phase cut-off (trailing edge):	NO
Built-in width:	-mm	Dimming phase cut-on (leading edge):	NO
With light sensor:	NO	Dimming programmable:	NO
Suitable for suspended mounting:	NO	Dimming RF:	NO
Luminous intensity:	-cd	Dimming Sine Wave Reduction:	NO
Number of poles:	-cd	Dimming Touch and Dim:	NO
Length:	-mm	Dimming Zigbee:	NO
Height/depth:	-mm	Dimming with push-button:	NO
Housing material:	-mm	No dim function:	NO
Lamp type:	-mm	Light distributor:	NO
Reflector colour:	-mm	Luminaire efficacy:	-lm/W
With presence detector:	NO	Suitable for low voltage cable system:	NO
Degree of protection (IP), front side:	NO	Dimming DSI:	NO
Built-in length:	-mm	Unified Glare Ratio (UGR):	NO
Light outlet:	-mm	Operation by Bluetooth:	NO
Light distribution:	-mm	Compatible with Apple HomeKit:	NO
Material cover:	-mm	Compatible with Google Assistant:	NO
Impact strength:	-mm	Compatible with Amazon Alexa:	NO
Nominal voltage:	NA V	Max. number of luminaires per miniature circuit breaker C16 (MCB):	NO
Emergency power supply integrated:	NO	Max. number of luminaires per miniature circuit breaker B16 (MCB):	NO
Degree of protection (IP):	NO	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	-%
With light source:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	-%
Covering of the luminaire with thermally insulating material possible:	NO	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Suitable for number of light sources:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Suitable for built-in mounting:	NO	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	-%
With control gear:	NO	Dimming DALI-2:	NO
Suitable for workplace according to EN 12464-1:	NO	Flickering value Pst LM:	NO
Suitable for surface mounting:	NO	Stroboscope effect value SVM:	NO

Beam angle:	NO	Colour of light adjustable:	NO
Connectable conductor cross section:	NA mm²	Luminous flux adjustable:	NO
Surface brushed:	NO	Beam angle adjustable:	NO
Luminous flux in emergency mode:	-lm	Exchangeable control gear:	NO
Nominal current:	NA mA	Built-in diameter:	NA mm
Colour temperature:	NA K	Compatible with Casambi:	NO
Max. system power:	-W	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Rated luminous flux according to IEC 62722-2-1:	-lm	Luminous intensity:	NA cd
Colour of light:	-lm	Degree of protection (IP), rear side:	NA cd
Adjustability:	-lm	Movement sensor/presence detector technology:	NA cd
Suitable for traverse mounting:	NO	Luminaire efficacy:	NA cd
Suitable for pedestal/floor mounting:	NO	Rated luminous flux according to IEC 62722-2-1:	NA cd
Suitable for light-track mounting:	NO	Emergency power supply system:	NA cd
Suitable for clamp-mounting:	NO	Power consumption in emergency mode:	NA cd
Constant light output (CLO):	NO	Emergency function monitoring system:	NA cd
Built-in height:	NA mm	Containing product according to 2019/2020/EU:	NA cd
IFTTT support available:	NO	Total harmonic distortion (THD):	NA cd
Luminous flux:	NA lm	Suitable for ceiling mounting:	NO
Type of wiring:	NA lm	Built-in length:	NO
Rated lifetime L70/B50 at 25 °C:	-h	Built-in height/depth:	-mm
Rated lifetime L80/B50 at 25 °C:	-h	Power factor:	-mm

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product
STATISTICS	94051900

