

Tubosa PENDEL 300/55 GU10 matte black + 1,5m black cable + black ceiling cap



Tubosa PENDEL 300/55 GU10 matte black + 1,5m black cable + black ceiling cap	
ARTICLE_NUMBER:	590056.00A
CHANGED_LAST:	17-09-2025
BRAND:	Daylightitalia
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001743 - Pendant luminaire
SYNONYM:	Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire



FEATURES

Protection class according to IEC 61140:	--	Degree of protection (NEMA):	-h
Width:	-mm	Filament test according to IEC 60695-2-11:	-h
Reflector:	-mm	Dimming 0-10 V:	NO
Lamp holder:	-mm	Dimming 1-10 V:	NO
Conductor cross section:	-mm ²	Dimming DALI:	NO
Connection type:	-mm ²	Dimming DMX:	NO
Housing colour:	-mm ²	Dimming potentiometer (integrated):	NO
Dimmable:	NO	Dimming LineSwitch:	NO
Voltage type:	NO	Dimming manufacturer's proprietary system:	NO
With movement sensor:	NO	Dimming mains voltage modulation:	NO
Suitable for lamp power:	NA W	Dimming phase cut-off (trailing edge):	NO
Type of grid:	NA W	Dimming phase cut-on (leading edge):	NO
Type of control gear:	NA W	Dimming programmable:	NO
Colour rendering index CRI:	NA W	Dimming RF:	NO
Diameter:	-mm	Dimming Sine Wave Reduction:	NO
With light sensor:	NO	Dimming Touch and Dim:	NO
Number of poles:	NO	Dimming Zigbee:	NO
Length:	-mm	Dimming with push-button:	NO
Height/depth:	-mm	No dim function:	NO
Housing material:	-mm	Light distributor:	NO
Lamp type:	-mm	Luminaire efficacy:	-lm/W
With presence detector:	NO	Dimming DSI:	NO
Direct-/indirect proportion separately controllable:	NO	Unified Glare Ratio (UGR):	NO
Suitable for light line configuration:	NO	Operation by Bluetooth:	NO
Suitable for emergency lighting:	NO	Compatible with Apple HomeKit:	NO
Light outlet:	NO	Compatible with Google Assistant:	NO
Light distribution:	NO	Compatible with Amazon Alexa:	NO
Material cover:	NO	Max. number of luminaires per miniature circuit breaker C16 (MCB):	NO
Pendant length:	NA mm	Max. number of luminaires per miniature circuit breaker B16 (MCB):	NO
Impact strength:	NA mm	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Nominal voltage:	NA V	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	-%
Emergency power supply integrated:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Degree of protection (IP):	NO	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	-%
With light source:	NO	Dimming DALI-2:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Flickering value Pst LM:	NO
Suitable for number of light sources:	NO	Stroboscope effect value SVM:	NO
With control gear:	NO	Colour of light adjustable:	NO
With suspension:	NO	Luminous flux adjustable:	NO
Suitable for workplace according to EN 12464-1:	NO	Beam angle adjustable:	NO
Connectable conductor cross section:	NA mm ²	Exchangeable control gear:	NO
Luminous flux in emergency mode:	-lm	Compatible with Casambi:	NO
Nominal current:	NA mA	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Colour temperature:	NA K	Movement sensor/presence detector technology:	NO
Max. system power:	-W	Luminaire efficacy:	NO

Rated luminous flux according to IEC 62722-2-1:	-lm	Rated luminous flux according to IEC 62722-2-1:	NO
Colour of light:	-lm	Emergency power supply system:	NO
Constant light output (CLO):	NO	Power consumption in emergency mode:	NO
IFTTT support available:	NO	Emergency function monitoring system:	NO
Type of wiring:	NO	Containing product according to 2019/2020/EU:	NO
Rated lifetime L70/B50 at 25 °C:	-h	Power factor:	NO

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product
STATISTICS	94051900

