

## Tubosa PENDEL 500/55 GU10 matte white + 1,5m white cable + white ceiling cap



|                                                                              |                                                                           |
|------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Tubosa PENDEL 500/55 GU10 matte white + 1,5m white cable + white ceiling cap |                                                                           |
| ARTICLE_NUMBER:                                                              | 590060.00A                                                                |
| CHANGED_LAST:                                                                | 17-09-2025                                                                |
| BRAND:                                                                       | Daylightitalia                                                            |
| ETIM_GROUP:                                                                  | EG000027 - Luminaires                                                     |
| ETIM_CLASS:                                                                  | EC001743 - Pendant luminaire                                              |
| SYNONYM:                                                                     | Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire |



## FEATURES

|                                                                                  |                    |                                                                                   |       |
|----------------------------------------------------------------------------------|--------------------|-----------------------------------------------------------------------------------|-------|
| Protection class according to IEC 61140:                                         | --                 | Degree of protection (NEMA):                                                      | -h    |
| Width:                                                                           | -mm                | Filament test according to IEC 60695-2-11:                                        | -h    |
| Reflector:                                                                       | -mm                | Dimming 0-10 V:                                                                   | NO    |
| Lamp holder:                                                                     | -mm                | Dimming 1-10 V:                                                                   | NO    |
| Conductor cross section:                                                         | -mm <sup>2</sup>   | Dimming DALI:                                                                     | NO    |
| Connection type:                                                                 | -mm <sup>2</sup>   | Dimming DMX:                                                                      | NO    |
| Housing colour:                                                                  | -mm <sup>2</sup>   | Dimming potentiometer (integrated):                                               | NO    |
| Dimmable:                                                                        | NO                 | Dimming LineSwitch:                                                               | NO    |
| Voltage type:                                                                    | NO                 | Dimming manufacturer's proprietary system:                                        | NO    |
| With movement sensor:                                                            | NO                 | Dimming mains voltage modulation:                                                 | NO    |
| Suitable for lamp power:                                                         | NA W               | Dimming phase cut-off (trailing edge):                                            | NO    |
| Type of grid:                                                                    | NA W               | Dimming phase cut-on (leading edge):                                              | NO    |
| Type of control gear:                                                            | NA W               | Dimming programmable:                                                             | NO    |
| Colour rendering index CRI:                                                      | NA W               | Dimming RF:                                                                       | NO    |
| Diameter:                                                                        | -mm                | Dimming Sine Wave Reduction:                                                      | NO    |
| With light sensor:                                                               | NO                 | Dimming Touch and Dim:                                                            | NO    |
| Number of poles:                                                                 | NO                 | Dimming Zigbee:                                                                   | NO    |
| Length:                                                                          | -mm                | Dimming with push-button:                                                         | NO    |
| Height/depth:                                                                    | -mm                | No dim function:                                                                  | NO    |
| Housing material:                                                                | -mm                | Light distributor:                                                                | NO    |
| Lamp type:                                                                       | -mm                | Luminaire efficacy:                                                               | -lm/W |
| With presence detector:                                                          | NO                 | Dimming DSI:                                                                      | NO    |
| Direct-/indirect proportion separately controllable:                             | NO                 | Unified Glare Ratio (UGR):                                                        | NO    |
| Suitable for light line configuration:                                           | NO                 | Operation by Bluetooth:                                                           | NO    |
| Suitable for emergency lighting:                                                 | NO                 | Compatible with Apple HomeKit:                                                    | NO    |
| Light outlet:                                                                    | NO                 | Compatible with Google Assistant:                                                 | NO    |
| Light distribution:                                                              | NO                 | Compatible with Amazon Alexa:                                                     | NO    |
| Material cover:                                                                  | NO                 | Max. number of luminaires per miniature circuit breaker C16 (MCB):                | NO    |
| Pendant length:                                                                  | NA mm              | Max. number of luminaires per miniature circuit breaker B16 (MCB):                | NO    |
| Impact strength:                                                                 | NA mm              | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):        | -%    |
| Nominal voltage:                                                                 | NA V               | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):        | -%    |
| Emergency power supply integrated:                                               | NO                 | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):             | -%    |
| Degree of protection (IP):                                                       | NO                 | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):             | -%    |
| With light source:                                                               | NO                 | Dimming DALI-2:                                                                   | NO    |
| Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | NO                 | Flickering value Pst LM:                                                          | NO    |
| Suitable for number of light sources:                                            | NO                 | Stroboscope effect value SVM:                                                     | NO    |
| With control gear:                                                               | NO                 | Colour of light adjustable:                                                       | NO    |
| With suspension:                                                                 | NO                 | Luminous flux adjustable:                                                         | NO    |
| Suitable for workplace according to EN 12464-1:                                  | NO                 | Beam angle adjustable:                                                            | NO    |
| Connectable conductor cross section:                                             | NA mm <sup>2</sup> | Exchangeable control gear:                                                        | NO    |
| Luminous flux in emergency mode:                                                 | -lm                | Compatible with Casambi:                                                          | NO    |
| Nominal current:                                                                 | NA mA              | Energy efficiency class of the light source according to EU regulation 2019/2015: | NO    |
| Colour temperature:                                                              | NA K               | Movement sensor/presence detector technology:                                     | NO    |
| Max. system power:                                                               | -W                 | Luminaire efficacy:                                                               | NO    |

|                                                 |     |                                                 |    |
|-------------------------------------------------|-----|-------------------------------------------------|----|
| Rated luminous flux according to IEC 62722-2-1: | -lm | Rated luminous flux according to IEC 62722-2-1: | NO |
| Colour of light:                                | -lm | Emergency power supply system:                  | NO |
| Constant light output (CLO):                    | NO  | Power consumption in emergency mode:            | NO |
| IFTTT support available:                        | NO  | Emergency function monitoring system:           | NO |
| Type of wiring:                                 | NO  | Containing product according to 2019/2020/EU:   | NO |
| Rated lifetime L70/B50 at 25 °C:                | -h  | Power factor:                                   | NO |

## PACKING\_INFORMATION

|              |                                                                                                                                                                                                                                                                                             |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEIGHT       | 0 gr                                                                                                                                                                                                                                                                                        |
| PACKING_CODE | BX                                                                                                                                                                                                                                                                                          |
| PACKING_FORM | Box<br><p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p> |
| STATISTICS   | 94051900                                                                                                                                                                                                                                                                                    |

