

Tubosa PLAF 300/45 E27 gold



Tubosa PLAF 300/45 E27 gold	
ARTICLE_NUMBER:	590064.00A
CHANGED_LAST:	17-09-2025
BRAND:	Daylightitalia
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC002892 - Ceiling-/wall luminaire
SYNONYM:	Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire



FEATURES

Protection class according to IEC 61140:	--	Colour consistency (McAdam ellipse):	-h
Width:	-mm	Total harmonic distortion:	-h
Outer diameter:	-mm	Photobiological safety according to EN 62471:	-h
Lamp holder:	-mm	Degree of protection (NEMA):	-h
Conductor cross section:	-mm ²	Rated ambient temperature according to IEC 62722-2-1:	NA °C
Connection type:	-mm ²	Filament test according to IEC 60695-2-11:	NA °C
Housing colour:	-mm ²	Dimming 0-10 V:	NO
Dimmable:	NO	Dimming 1-10 V:	NO
With connection cord and plug:	NO	Dimming DALI:	NO
Voltage type:	NO	Dimming DMX:	NO
With movement sensor:	NO	Dimming potentiometer (integrated):	NO
Suitable for lamp power:	NA W	Dimming LineSwitch:	NO
Type of grid:	NA W	Dimming manufacturer's proprietary system:	NO
Length of power cord:	-mm	Dimming mains voltage modulation:	NO
Type of control gear:	-mm	Dimming phase cut-off (trailing edge):	NO
Colour rendering index CRI:	-mm	Dimming phase cut-on (leading edge):	NO
Suitable for wall mounting:	NO	Dimming programmable:	NO
Built-in width:	-mm	Dimming RF:	NO
Built-in diameter:	-mm	Dimming Sine Wave Reduction:	NO
With switch:	NO	Dimming Touch and Dim:	NO
With light sensor:	NO	Dimming Zigbee:	NO
Suitable for suspended mounting:	NO	Dimming with push-button:	NO
Luminous intensity:	-cd	No dim function:	NO
Number of poles:	-cd	Light distributor:	NO
Length:	-mm	Luminaire efficacy:	-lm/W
Height/depth:	-mm	Dimming DSI:	NO
Housing material:	-mm	Unified Glare Ratio (UGR):	NO
Lamp type:	-mm	Operation by Bluetooth:	NO
With presence detector:	NO	Compatible with Apple HomeKit:	NO
Degree of protection (IP), front side:	NO	Compatible with Google Assistant:	NO
Built-in length:	-mm	Compatible with Amazon Alexa:	NO
Suitable for light line configuration:	NO	Max. number of luminaires per miniature circuit breaker C16 (MCB):	NO
Suitable for emergency lighting:	NO	Max. number of luminaires per miniature circuit breaker B16 (MCB):	NO
Light outlet:	NO	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Light distribution:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Material cover:	NO	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	-%
Impact strength:	NO	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Nominal voltage:	NA V	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Emergency power supply integrated:	NO	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	-%
Degree of protection (IP):	NO	Dimming DALI-2:	NO
With light source:	NO	Flickering value Pst LM:	NO
With mounting material:	NO	Stroboscope effect value SVM:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Colour of light adjustable:	NO
Covering of the luminaire with thermally insulating material possible:	NO	Luminous flux adjustable:	NO

Suitable for number of light sources:	NO	Beam angle adjustable:	NO
Suitable for built-in mounting:	NO	Exchangeable control gear:	NO
With control gear:	NO	Compatible with Casambi:	NO
Suitable for workplace according to EN 12464-1:	NO	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Suitable for surface mounting:	NO	Luminous intensity:	NA cd
Beam angle:	NO	Degree of protection (IP), rear side:	NA cd
Connectable conductor cross section:	NA mm²	Movement sensor/presence detector technology:	NA cd
Luminous flux in emergency mode:	-lm	Luminaire efficacy:	NA cd
Nominal current:	NA mA	Rated luminous flux according to IEC 62722-2-1:	NA cd
Colour temperature:	NA K	Emergency power supply system:	NA cd
Max. system power:	-W	Power consumption in emergency mode:	NA cd
Rated luminous flux according to IEC 62722-2-1:	-lm	Emergency function monitoring system:	NA cd
Colour of light:	-lm	Containing product according to 2019/2020/EU:	NA cd
With air slots:	NO	Total harmonic distortion (THD):	NA cd
Suitable for clamp-mounting:	NO	Max. number of luminaires per miniature circuit breaker C10 (MCB):	NA cd
Constant light output (CLO):	NO	Suitable for ceiling mounting:	NO
IFTTT support available:	NO	Built-in height/depth:	-mm
Type of wiring:	NO	Surface protection housing:	-mm
Rated lifetime L70/B50 at 25 °C:	-h	Power factor:	-mm
Rated lifetime L80/B50 at 25 °C:	-h	Meets min. EIA service life criterion L90 (at 50,000 hours at tq = 25°C):	NO

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product
STATISTICS	94051900

