

Cable Trunking with Rem. Cover and Adhesive Tape 2m 20X10 TH



Cable Trunking with Rem. Cover and Adhesive Tape 2m 20X10 TH

ARTICLE_NUMBER: TH 15247

CHANGED_LAST: 18-09-2025

BRAND: Thorgeon

ETIM_GROUP: EG000004 - Cable carrying systems

ETIM_CLASS: EC000047 - Cable tray

SYNONYM: Cable duct, Cable support system, Cable tray, Cable tray/wide span cable tray, Cable trough, Ceiling cable tray, Ceiling cable tray system, Connector, Luminaire carrier tray



FEATURES

Colour:	White	Suitable for circuit integrity:	NO
Width:	102 mm	With cover:	NO
Model:	Without connector	Load test type according to IEC 61537:	NO
Height:	20 mm	Possible support spacing:	NA m
Type of connection:	20 mm	Safe working load according to IEC 61537 with support spacing 0.5 m:	-N/m
RAL-number:	9010	Safe working load according to IEC 61537 with support spacing 1.0 m:	-N/m
Surface protection:	Untreated	Safe working load according to IEC 61537 with support spacing 1.5 m:	-N/m
Connector design:	Untreated	Safe working load according to IEC 61537 with support spacing 2.0 m:	-N/m
Weight:	-kg/m	Safe working load according to IEC 61537 with support spacing 2.5 m:	-N/m
Material thickness:	-mm	Safe working load according to IEC 61537 with support spacing 3.0 m:	-N/m
Side perforation:	NO	Safe working load according to IEC 61537 with support spacing 4.0 m:	-N/m
Material quality:	Polyvinyl chloride (PVC)	Safe working load according to IEC 61537 with support spacing 5.0 m:	-N/m
Length:	2000 mm	Safe working load according to IEC 61537 with support spacing 6.0 m:	-N/m
Working temperature:	NA °C	Safe working load according to IEC 61537 with support spacing 7.0 m:	-N/m
Material:	Plastic	Safe working load according to IEC 61537 with support spacing 8.0 m:	-N/m
Bottom perforation:	NO	Safe working load according to IEC 61537 with support spacing 10.0 m:	-N/m
Usable cross section:	-mm²	Safe working load according to IEC 61537 with support spacing 9.0 m:	-N/m
NATO-mounting holes:	NO	Safe working load according to IEC 61537 with support spacing 11.0 m:	-N/m
Working length:	-mm	Safe working load according to IEC 61537 with support spacing 12.0 m:	-N/m

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p>
STATISTICS	73089098