

Elba pendel brass Car brass Caramella 150 E27 2700K porcelain



ARTICLE_NUMBER:	810090.00A
CHANGED_LAST:	25-09-2025
BRAND:	Daylight Italia
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001743 - Pendant luminaire
SYNONYM:	Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire



FEATURES

Protection class according to IEC 61140:	--	Degree of protection (NEMA):	15000 h
Width:	-mm	Filament test according to IEC 60695-2-11:	15000 h
Reflector:	None	Dimming 0-10 V:	NO
Lamp holder:	E27	Dimming 1-10 V:	NO
Conductor cross section:	-mm ²	Dimming DALI:	NO
Connection type:	-mm ²	Dimming DMX:	NO
Housing colour:	Brass	Dimming potentiometer (integrated):	NO
Dimmable:	YES	Dimming LineSwitch:	NO
Voltage type:	YES	Dimming manufacturer's proprietary system:	NO
With movement sensor:	NO	Dimming mains voltage modulation:	NO
Suitable for lamp power:	13 W	Dimming phase cut-off (trailing edge):	YES
Type of grid:	13 W	Dimming phase cut-on (leading edge):	NO
Type of control gear:	Not required	Dimming programmable:	NO
Colour rendering index CRI:	90-100	Dimming RF:	NO
Diameter:	150 mm	Dimming Sine Wave Reduction:	NO
With light sensor:	NO	Dimming Touch and Dim:	NO
Number of poles:	NO	Dimming Zigbee:	NO
Length:	314 mm	Dimming with push-button:	NO
Height/depth:	-mm	No dim function:	NO
Housing material:	Plastic	Light distributor:	None
Lamp type:	LED exchangeable	Luminaire efficacy:	117 lm/W
With presence detector:	NO	Dimming DSI:	NO
Direct-/indirect proportion separately controllable:	NO	Unified Glare Ratio (UGR):	NO
Suitable for light line configuration:	NO	Operation by Bluetooth:	NO
Suitable for emergency lighting:	NO	Compatible with Apple HomeKit:	NO
Light outlet:	Direct	Compatible with Google Assistant:	NO
Light distribution:	Direct	Compatible with Amazon Alexa:	NO
Material cover:	Direct	Max. number of luminaires per miniature circuit breaker C16 (MCB):	NO
Pendant length:	1500 mm	Max. number of luminaires per miniature circuit breaker B16 (MCB):	NO
Impact strength:	1500 mm	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Nominal voltage:	220 ~ 240	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	-%
Emergency power supply integrated:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Degree of protection (IP):	IP20	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	-%
With light source:	YES	Dimming DALI-2:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Flickering value Pst LM:	NO
Suitable for number of light sources:	1	Stroboscope effect value SVM:	NO
With control gear:	NO	Colour of light adjustable:	No
With suspension:	YES	Luminous flux adjustable:	No
Suitable for workplace according to EN 12464-1:	NO	Beam angle adjustable:	No
Connectable conductor cross section:	- mm ²	Exchangeable control gear:	NO
Luminous flux in emergency mode:	-lm	Compatible with Casambi:	NO
Nominal current:	- mA	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Colour temperature:	2700 K	Movement sensor/presence detector technology:	NO
Max. system power:	-W	Luminaire efficacy:	NO

Rated luminous flux according to IEC 62722-2-1: 1521 lm

Colour of light: White

Constant light output (CLO): NO

IFTTT support available: NO

Type of wiring: NO

Rated lifetime L70/B50 at 25 °C: 15000 h

Rated luminous flux according to IEC 62722-2-1: NO

Emergency power supply system: NO

Power consumption in emergency mode: NO

Emergency function monitoring system: NO

Containing product according to 2019/2020/EU: NO

Power factor: NO

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product
STATISTICS	94051041

