

## Elba pendel black Car black Caramella 150 E27 2700K clear



|                 |                                                                           |
|-----------------|---------------------------------------------------------------------------|
| ARTICLE_NUMBER: | 810094.00A                                                                |
| CHANGED_LAST:   | 25-09-2025                                                                |
| BRAND:          | Daylight Italia                                                           |
| ETIM_GROUP:     | EG000027 - Luminaires                                                     |
| ETIM_CLASS:     | EC001743 - Pendant luminaire                                              |
| SYNONYM:        | Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire |



## FEATURES

|                                                                                  |                   |                                                                                   |          |
|----------------------------------------------------------------------------------|-------------------|-----------------------------------------------------------------------------------|----------|
| Protection class according to IEC 61140:                                         | --                | Degree of protection (NEMA):                                                      | 15000 h  |
| Width:                                                                           | -mm               | Filament test according to IEC 60695-2-11:                                        | 15000 h  |
| Reflector:                                                                       | None              | Dimming 0-10 V:                                                                   | NO       |
| Lamp holder:                                                                     | E27               | Dimming 1-10 V:                                                                   | NO       |
| Conductor cross section:                                                         | -mm <sup>2</sup>  | Dimming DALI:                                                                     | NO       |
| Connection type:                                                                 | -mm <sup>2</sup>  | Dimming DMX:                                                                      | NO       |
| Housing colour:                                                                  | Black             | Dimming potentiometer (integrated):                                               | NO       |
| Dimmable:                                                                        | YES               | Dimming LineSwitch:                                                               | NO       |
| Voltage type:                                                                    | YES               | Dimming manufacturer's proprietary system:                                        | NO       |
| With movement sensor:                                                            | NO                | Dimming mains voltage modulation:                                                 | NO       |
| Suitable for lamp power:                                                         | 13 W              | Dimming phase cut-off (trailing edge):                                            | YES      |
| Type of grid:                                                                    | 13 W              | Dimming phase cut-on (leading edge):                                              | NO       |
| Type of control gear:                                                            | Not required      | Dimming programmable:                                                             | NO       |
| Colour rendering index CRI:                                                      | 90-100            | Dimming RF:                                                                       | NO       |
| Diameter:                                                                        | 150 mm            | Dimming Sine Wave Reduction:                                                      | NO       |
| With light sensor:                                                               | NO                | Dimming Touch and Dim:                                                            | NO       |
| Number of poles:                                                                 | NO                | Dimming Zigbee:                                                                   | NO       |
| Length:                                                                          | 314 mm            | Dimming with push-button:                                                         | NO       |
| Height/depth:                                                                    | -mm               | No dim function:                                                                  | NO       |
| Housing material:                                                                | Plastic           | Light distributor:                                                                | None     |
| Lamp type:                                                                       | LED exchangeable  | Luminaire efficacy:                                                               | 117 lm/W |
| With presence detector:                                                          | NO                | Dimming DSI:                                                                      | NO       |
| Direct-/indirect proportion separately controllable:                             | NO                | Unified Glare Ratio (UGR):                                                        | NO       |
| Suitable for light line configuration:                                           | NO                | Operation by Bluetooth:                                                           | NO       |
| Suitable for emergency lighting:                                                 | NO                | Compatible with Apple HomeKit:                                                    | NO       |
| Light outlet:                                                                    | Direct            | Compatible with Google Assistant:                                                 | NO       |
| Light distribution:                                                              | Direct            | Compatible with Amazon Alexa:                                                     | NO       |
| Material cover:                                                                  | Direct            | Max. number of luminaires per miniature circuit breaker C16 (MCB):                | NO       |
| Pendant length:                                                                  | 1500 mm           | Max. number of luminaires per miniature circuit breaker B16 (MCB):                | NO       |
| Impact strength:                                                                 | 1500 mm           | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):        | -%       |
| Nominal voltage:                                                                 | 220 ~ 240         | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):        | -%       |
| Emergency power supply integrated:                                               | NO                | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):             | -%       |
| Degree of protection (IP):                                                       | IP20              | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):             | -%       |
| With light source:                                                               | YES               | Dimming DALI-2:                                                                   | NO       |
| Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | NO                | Flickering value Pst LM:                                                          | NO       |
| Suitable for number of light sources:                                            | 1                 | Stroboscope effect value SVM:                                                     | NO       |
| With control gear:                                                               | NO                | Colour of light adjustable:                                                       | No       |
| With suspension:                                                                 | YES               | Luminous flux adjustable:                                                         | No       |
| Suitable for workplace according to EN 12464-1:                                  | NO                | Beam angle adjustable:                                                            | No       |
| Connectable conductor cross section:                                             | - mm <sup>2</sup> | Exchangeable control gear:                                                        | NO       |
| Luminous flux in emergency mode:                                                 | -lm               | Compatible with Casambi:                                                          | NO       |
| Nominal current:                                                                 | - mA              | Energy efficiency class of the light source according to EU regulation 2019/2015: | NO       |
| Colour temperature:                                                              | 2700 K            | Movement sensor/presence detector technology:                                     | NO       |
| Max. system power:                                                               | -W                | Luminaire efficacy:                                                               | NO       |

Rated luminous flux according to IEC 62722-2-1: 1521 lm

Colour of light: White

Constant light output (CLO): NO

IFTTT support available: NO

Type of wiring: NO

Rated lifetime L70/B50 at 25 °C: 15000 h

Rated luminous flux according to IEC 62722-2-1: NO

Emergency power supply system: NO

Power consumption in emergency mode: NO

Emergency function monitoring system: NO

Containing product according to 2019/2020/EU: NO

Power factor: NO

## PACKING\_INFORMATION

|              |                                                                                                                                                                                                                                                                                             |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEIGHT       | 0 gr                                                                                                                                                                                                                                                                                        |
| PACKING_CODE | BX                                                                                                                                                                                                                                                                                          |
| PACKING_FORM | Box<br><p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p> |
| STATISTICS   | 94051041                                                                                                                                                                                                                                                                                    |

