

LED emergency 220-240V 5W 6000K 3hrs. battery Thorgeon



LED emergency 220-240V 5W 6000K 3hrs. battery Thorgeon	
ARTICLE_NUMBER:	TH 03028
CHANGED_LAST:	07-10-2025
BRAND:	Thorgeon
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001957 - Emergency luminaire
SYNONYM:	Emergency luminaire, Transparent



FEATURES

Mounting method:	Wall surface mounting/ceiling surface mounting	Recognition distance:	30 m
Protection class according to IEC 61140:	II	Nominal current:	30 m
Width:	310 mm	Colour temperature:	6000 ~ 6500
Outer diameter:	-mm	Max. system power:	5 W
Function:	Escape route signage	Rated luminous flux according to IEC 62722-2-1:	-lm
Lamp holder:	Escape route signage	Constant light output (CLO):	NO
Conductor cross section:	-mm ²	With pictogram:	YES
Connection type:	-mm ²	Type of wiring:	YES
Housing colour:	White	Rated lifetime L70/B50 at 25 °C:	-h
Voltage type:	AC	Luminous flux in standby mode:	50 lm
Power supply system:	AC	Degree of protection (NEMA):	50 lm
Type of control gear:	AC	Rated ambient temperature according to IEC 62722-2-1:	- °C
With remote control:	NO	Light distributor:	- °C
Built-in width:	-mm	RAL-number housing:	- °C
Built-in diameter:	-mm	Nominal operation time:	3 h
Suitable for labelling type:	-mm	Max. number of luminaires per miniature circuit breaker C16 (MCB):	3 h
Type of indicator:	-mm	Max. number of luminaires per miniature circuit breaker B16 (MCB):	3 h
Number of poles:	-mm	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Length:	63.3 mm	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	-%
Height/depth:	135.9 mm	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Housing material:	Other	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	-%
Lamp type:	LED not exchangeable	Flickering value Pst LM:	-%
Number of lighting heads:	LED not exchangeable	Stroboscope effect value SVM:	-%
Built-in length:	-mm	Exchangeable control gear:	NO
Material cover:	-mm	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Impact strength:	-mm	Suitable for standby switching:	NO
Battery technology:	Lithium-ion	Suitable for continuous circuit:	NO
Nominal voltage:	220 ~ 240	Rated luminous flux according to IEC 62722-2-1:	NO
Degree of protection (IP):	IP65	Emergency power supply system:	NO
With light source:	YES	Power consumption in emergency mode:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Emergency function monitoring system:	NO
Suitable for number of light sources:	NO	With heating element for battery:	NO
With remote switch connection:	NO	Type of lithium-ion battery:	NO
Monitoring equipment:	NO	Built-in height/depth:	-mm
Connectable conductor cross section:	NO	Power factor:	0.4

PACKING_INFORMATION

WEIGHT	0.92 kg
WIDTH	362 mm
HEIGHT	310 mm
LENGHT	470 mm

PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p>
STATISTICS	85395100

