


## Outdoor Wall Light 2xGU10 IP65 Square Anthracite without lamp



|   |  |
|---|--|
| Outdoor Wall Light 2xGU10 IP65 Square Anthracite without lamp |  |
| ARTICLE_NUMBER:   | TH 03116   |
| CHANGED_LAST:   | 30-09-2025   |
| BRAND:  | Thorgeon   |
| ETIM_GROUP:   | EG000027 - Luminaires  |
| ETIM_CLASS:   | EC002892 - Ceiling-/wall luminaire   |
| SYNONYM:  | Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire |



## FEATURES

|  |                      |  |       |
|--|----------------------|--|-------|
| Protection class according to IEC 61140:   | --                   | Colour consistency (McAdam ellipse):                                       | -h    |
| Width:   | 77 mm                | Total harmonic distortion:   | -h    |
| Outer diameter:  | -mm                  | Photobiological safety according to EN 62471:                              | -h    |
| Lamp holder:   | GU10                 | Degree of protection (NEMA):   | -h    |
| Conductor cross section:   | -mm <sup>2</sup>     | Rated ambient temperature according to IEC 62722-2-1:                      | - °C  |
| Connection type:   | Cable                | Filament test according to IEC 60695-2-11:                                 | - °C  |
| Housing colour:  | Anthracite           | Dimming 0-10 V:  | NO    |
| Dimmable:  | NO                   | Dimming 1-10 V:  | NO    |
| With connection cord and plug:   | NO                   | Dimming DALI:  | NO    |
| Voltage type:  | NO                   | Dimming DMX:   | NO    |
| With movement sensor:  | NO                   | Dimming potentiometer (integrated):  | NO    |
| Suitable for lamp power:   | - W                  | Dimming LineSwitch:  | NO    |
| Type of grid:  | None                 | Dimming manufacturer's proprietary system:                                 | NO    |
| Length of power cord:  | -mm                  | Dimming mains voltage modulation:  | NO    |
| Type of control gear:  | Not required         | Dimming phase cut-off (trailing edge):                                     | NO    |
| Colour rendering index CRI:  | Not required         | Dimming phase cut-on (leading edge):                                       | NO    |
| Suitable for wall mounting:  | YES                  | Dimming programmable:  | NO    |
| Built-in width:  | -mm                  | Dimming RF:  | NO    |
| Built-in diameter:   | -mm                  | Dimming Sine Wave Reduction:   | NO    |
| With switch:   | NO                   | Dimming Touch and Dim:   | NO    |
| With light sensor:   | NO                   | Dimming Zigbee:  | NO    |
| Suitable for suspended mounting:   | NO                   | Dimming with push-button:  | NO    |
| Luminous intensity:  | -cd                  | No dim function:   | NO    |
| Number of poles:   | -cd                  | Light distributor:   | NO    |
| Length:  | 161 mm               | Luminaire efficacy:  | -lm/W |
| Height/depth:  | 68 mm                | Dimming DSI:   | NO    |
| Housing material:  | Plastic              | Unified Glare Ratio (UGR):   | NO    |
| Lamp type:   | LED exchangeable     | Operation by Bluetooth:  | NO    |
| With presence detector:  | NO                   | Compatible with Apple HomeKit:   | NO    |
| Degree of protection (IP), front side:   | NO                   | Compatible with Google Assistant:  | NO    |
| Built-in length:   | -mm                  | Compatible with Amazon Alexa:  | NO    |
| Suitable for light line configuration:   | NO                   | Max. number of luminaires per miniature circuit breaker C16 (MCB):         | NO    |
| Suitable for emergency lighting:   | NO                   | Max. number of luminaires per miniature circuit breaker B16 (MCB):         | NO    |
| Light outlet:  | NO                   | Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq): | -%    |
| Light distribution:  | NO                   | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | -%    |
| Material cover:  | Plastic, transparent | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq): | -%    |
| Impact strength:   | Plastic, transparent | Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):      | -%    |
| Nominal voltage:   | 220 ~ 240            | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):      | -%    |
| Emergency power supply integrated:   | NO                   | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):      | -%    |
| Degree of protection (IP):   | IP65                 | Dimming DALI-2:  | NO    |
| With light source:   | NO                   | Flickering value Pst LM:   | NO    |
| With mounting material:  | YES                  | Stroboscope effect value SVM:  | NO    |
| Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | NO                   | Colour of light adjustable:  | NO    |
| Covering of the luminaire with thermally insulating material possible:           | NO                   | Luminous flux adjustable:  | NO    |

|   |                   |   |           |
|---|-------------------|---|-----------|
| Suitable for number of light sources:           | 2                 | Beam angle adjustable:  | NO        |
| Suitable for built-in mounting:                 | NO                | Exchangeable control gear:  | NO        |
| With control gear:                              | NO                | Compatible with Casambi:  | NO        |
| Suitable for workplace according to EN 12464-1: | NO                | Energy efficiency class of the light source according to EU regulation 2019/2015: | NO        |
| Suitable for surface mounting:                  | YES               | Luminous intensity:   | - cd      |
| Beam angle:                                     | YES               | Degree of protection (IP), rear side:   | - cd      |
| Connectable conductor cross section:            | - mm <sup>2</sup> | Movement sensor/presence detector technology:                                     | - cd      |
| Luminous flux in emergency mode:                | -lm               | Luminaire efficacy:   | - cd      |
| Nominal current:                                | - mA              | Rated luminous flux according to IEC 62722-2-1:                                   | - cd      |
| Colour temperature:                             | - K               | Emergency power supply system:  | - cd      |
| Max. system power:                              | 35 W              | Power consumption in emergency mode:  | - cd      |
| Rated luminous flux according to IEC 62722-2-1: | -lm               | Emergency function monitoring system:   | - cd      |
| Colour of light:                                | -lm               | Containing product according to 2019/2020/EU:                                     | - cd      |
| With air slots:                                 | NO                | Total harmonic distortion (THD):  | - cd      |
| Suitable for clamp-mounting:                    | NO                | Max. number of luminaires per miniature circuit breaker C10 (MCB):                | - cd      |
| Constant light output (CLO):                    | NO                | Suitable for ceiling mounting:  | NO        |
| IFTTT support available:                        | NO                | Built-in height/depth:  | -mm       |
| Type of wiring:                                 | NO                | Surface protection housing:   | Lacquered |
| Rated lifetime L70/B50 at 25 °C:                | -h                | Power factor:   | Lacquered |
| Rated lifetime L80/B50 at 25 °C:                | -h                | Meets min. EIA service life criterion L90 (at 50,000 hours at tq = 25°C):         | NO        |

## PACKING\_INFORMATION

|              |   |
|--------------|---|
| WEIGHT       | 0 gr  |
| PACKING_CODE | BX  |
| PACKING_FORM | Box<br><p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p> |
| STATISTICS   | 94051190  |

