

Outdoor rotatable LED Spike Light 1xGU10 IP65 Anthrasite



Outdoor rotatable LED Spike Light 1xGU10 IP65 Anthrasite	
ARTICLE_NUMBER:	TH 03123
CHANGED_LAST:	01-10-2025
BRAND:	Thorgeon
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC000301 - Luminaire bollard
SYNONYM:	Bollard, Bollard luminaire, Luminaire bollard, Orientation luminaire, Pedestal luminaire, Stele



FEATURES

Protection class according to IEC 61140:	--	Colour temperature:	NA K
Width:	-mm	Max. system power:	35 W
Lamp holder:	GU10	Rated luminous flux according to IEC 62722-2-1:	-lm
Conductor cross section:	-mm²	Colour of light:	-lm
With base plate:	NO	Constant light output (CLO):	NO
Connection type:	Free conductor end	IFTTT support available:	NO
Housing colour:	Anthracite	Type of wiring:	NO
Surface protection:	Lacquered	Rated lifetime L70/B50 at 25 °C:	-h
Voltage type:	AC	Degree of protection (NEMA):	-h
With movement sensor:	NO	Light distributor:	-h
Suitable for lamp power:	NA W	Luminaire efficacy:	-lm/W
Type of control gear:	Not required	Compatible with Apple HomeKit:	NO
Colour rendering index CRI:	Not required	Compatible with Google Assistant:	NO
Diameter:	-mm	Compatible with Amazon Alexa:	NO
With light sensor:	NO	Max. number of luminaires per miniature circuit breaker C16 (MCB):	NO
Luminous intensity:	-cd	Max. number of luminaires per miniature circuit breaker B16 (MCB):	NO
Number of poles:	-cd	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Length:	65 mm	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	-%
Height/depth:	408 mm	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Type of power supply:	408 mm	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	-%
Housing material:	Plastic	Flickering value Pst LM:	-%
Lamp type:	LED exchangeable	Stroboscope effect value SVM:	-%
Type of luminaire:	Ground spike	Colour of light adjustable:	-%
Light outlet:	Ground spike	Luminous flux adjustable:	-%
Light distribution:	Ground spike	Beam angle adjustable:	-%
Material cover:	Plastic, transparent	Exchangeable control gear:	NO
Impact strength:	Plastic, transparent	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Nominal voltage:	NA V	Luminous intensity:	NA cd
Degree of protection (IP):	IP54	Movement sensor/presence detector technology:	NA cd
With light source:	NO	Rated luminous flux according to IEC 62722-2-1:	NA cd
Suitable for number of light sources:	1	Containing product according to 2019/2020/EU:	NA cd
With control gear:	NO	Housing material quality:	NA cd
Beam angle:	NO	Power factor:	NA cd
Connectable conductor cross section:	NA mm²	Meets min. EIA service life criterion L90 (at 50,000 hours at tq = 25°C):	NO

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p>

STATISTICS 94051190

