

Mini led profile 300mm 24V DC 5W 2700K 300Lm IP20 Thorgeon



| | |
|--|--|
| Mini led profile 300mm 24V DC 5W 2700K 300Lm IP20 Thorgeon | |
| ARTICLE_NUMBER: | TH 07003 |
| CHANGED_LAST: | 09-12-2025 |
| BRAND: | Thorgeon |
| ETIM_GROUP: | EG000027 - Luminaires |
| ETIM_CLASS: | EC002706 - Light ribbon-/hose/-strip |
| SYNONYM: | LED, LED strip, LED-light ribbon-/hose/-strip, LED-strip, Light ribbon-/hose/-strip, Single LED, Light hose, Light ribbon, Light strip |



FEATURES

| | | | |
|--|----------------------|---|-------------|
| Mounting method: | Surface mounting | With end piece: | YES |
| Protection class according to IEC 61140: | Surface mounting | Number of nodes per meter: | YES |
| Width: | 18 mm | Lamp voltage: | 24 V |
| Model: | Strip | Colour temperature: | 3000 ~ 6000 |
| Conductor cross section: | -mm ² | Max. system power: | -W |
| Connection type: | Other | Colour of light: | White |
| Beam angle: | 100 ° | Constant light output (CLO): | NO |
| Voltage type: | 100 ° | Luminous flux per meter: | 350 lm |
| Total length: | -m | IFTTT support available: | NO |
| Type of control gear: | -m | Type of wiring: | NO |
| Self-adhesive: | NO | Rated lifetime L70/B50 at 25 °C: | 4000 h |
| Colour rendering index CRI: | 80-89 | Degree of protection (NEMA): | 4000 h |
| Diameter: | -mm | Lamp power per foot: | -W |
| Suitable for dimmer: | YES | Luminaire efficacy: | 116 lm/W |
| Number of poles: | YES | Number of nodes per foot: | 116 lm/W |
| Length: | 300 mm | Compatible with Apple HomeKit: | NO |
| Height/depth: | -mm | Compatible with Google Assistant: | NO |
| Type of power supply: | Mains power supply | Compatible with Amazon Alexa: | NO |
| Lamp type: | LED not exchangeable | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 70 % |
| Degree of protection (IP): | IP20 | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | -% |
| With protective cover: | YES | Colour of light adjustable: | -% |
| Connectable conductor cross section: | NA mm ² | Luminous flux adjustable: | -% |
| Lowest bending radius: | -mm | Beam angle adjustable: | -% |
| Lamp power per meter: | 5 W | Exchangeable control gear: | NO |
| Length of particular segments: | -mm | Energy efficiency class of the light source according to EU regulation 2019/2015: | G |
| With connection set: | YES | Power factor: | G |

PACKING_INFORMATION

| | |
|--------------|---|
| WEIGHT | 0 kg |
| PACKING_CODE | BX |
| PACKING_FORM | Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product.</p> |
| STATISTICS | 85395100 |

