

LED Ba15s Tube T18x45 230V 3W 250Lm 830 AC Clear non-Dim



SDCM3; High lumen with compact size; Marine and automotive application;

ARTICLE_NUMBER: SPL151922330

CHANGED_LAST: 19-01-2026

BRAND: SPL,Schiefer

ETIM_GROUP: EG000028 - Lamps

ETIM_CLASS: EC001959 - LED-lamp/Multi-LED

SYNONYM: Bulblamp, Candlelamp, Globelamp,
Lamp, LED, LED candle, LED capsule,
LED lamp, LED luster



FEATURES

Colour:	White	Lamp power:	3.000 W
Socket:	BA15s	Luminous flux:	225.000 ~ 275.000
Housing colour:	BA15s	Colour consistency (McAdam ellipse):	SDCM3
Dimmable:	NO	Total harmonic distortion:	SDCM3
Voltage type:	AC	Photobiological safety according to EN 62471:	RG0
With movement sensor:	NO	Dimming phase cut-off (trailing edge):	NO
With twilight switch:	NO	Dimming phase cut-on (leading edge):	NO
Colour rendering index CRI:	80-89	Dimming Touch and Dim:	NO
With remote control:	NO	Dimming Zigbee:	NO
Diameter:	18 mm	No dim function:	YES
Suitable for electronic ballast:	NO	Lamp designation:	Other
Lamp efficacy:	83.33 lm/W	Filament lamp:	NO
Luminous intensity:	-cd	Min. number of switching cycles:	50000
Lamp shape:	Tube, single-ended	Beam angle:	360.000 °
Length:	45 mm	Rated luminous flux according to IEC 62612:	250 lm
Remote operation possible:	NO	Compatible with Apple HomeKit:	NO
Nominal voltage:	220.000 ~ 235.000	Compatible with Google Assistant:	NO
Degree of protection (IP):	IP20	Compatible with Amazon Alexa:	NO
Colour of light according to EN 12464-1:	Warm white < 3300 K	Suitable for magnetic ballast:	NO
Type of glass/cover:	Clear	Energy efficiency class according to EU regulation 2019/2015:	G
Average nominal lifetime:	30000 h	Dimming Bluetooth:	NO
Nominal current:	13.000 ~ 14.000	Dimming Wi-Fi:	NO
Colour temperature:	3000.000 K	Material of light bulb:	NO
Weighted energy consumption in 1000 hours:	3 kWh	Total harmonic distortion (THD):	NO
IFTTT support available:	NO	Power factor:	0.4

PACKING_INFORMATION

WEIGHT	0.02 kg
WIDTH	0.03 m
HEIGHT	0.06 m
LENGHT	0.03 m
PACKING_CODE	CT
PACKING_FORM	Cardboard A cardboard box or container
STATISTICS	85395200

