




LED Floodlight PRO 300W 4000K 42000Lm IP66 IK08 Thorgeon



LED Floodlight PRO 300W 4000K 42000Lm IP66 IK08 Thorgeon

ARTICLE_NUMBER: TH 03076

CHANGED_LAST: 27-01-2026

BRAND: Thorgeon

ETIM_GROUP: EG000027 - Luminaires

ETIM_CLASS: EC001744 - Downlight/spot/floodlight

SYNONYM: Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight



FEATURES

Protection class according to IEC 61140: I	Built-in width: NA mm
Width: 399 mm	Colour consistency (McAdam ellipse): Other
Outer diameter: -mm	Total harmonic distortion: 10
Reflector: None	Photobiological safety according to EN 62471: Other
Lamp holder: None	Degree of protection (NEMA): Other
Conductor cross section: 1 mm ²	Rated ambient temperature according to IEC 62722-2-1: -30 ~ 45
Connection type: 1 mm ²	Filament test according to IEC 60695-2-11: -30 ~ 45
Housing colour: Grey	Dimming 0-10 V: NO
Dimmable: NO	Dimming 1-10 V: YES
Surface protection: Other	Dimming DALI: NO
Voltage type: AC	Dimming DMX: NO
With movement sensor: NO	Dimming potentiometer (integrated): YES
Suitable for lamp power: 300 W	Dimming LineSwitch: NO
Type of control gear: LED operating device current-controlled	Dimming manufacturer's proprietary system: NO
Colour rendering index CRI: 70-79	Dimming mains voltage modulation: NO
Suitable for wall mounting: YES	Dimming phase cut-off (trailing edge): NO
Built-in width: -mm	Dimming phase cut-on (leading edge): NO
With light sensor: NO	Dimming programmable: NO
Suitable for suspended mounting: NO	Dimming RF: NO
Luminous intensity: 16068 cd	Dimming Sine Wave Reduction: NO
Number of poles: 1	Dimming Touch and Dim: NO
Length: 611 mm	Dimming Zigbee: NO
Height/depth: 65 mm	Dimming with push-button: NO
Housing material: Aluminium	No dim function: NO
Lamp type: LED not exchangeable	Light distributor: Diffuser lens/optic/panel
Reflector colour: LED not exchangeable	Luminaire efficacy: 140 lm/W
With presence detector: NO	Suitable for low voltage cable system: NO
Degree of protection (IP), front side: NO	Dimming DSI: NO
Built-in length: -mm	Unified Glare Ratio (UGR): NO
Light outlet: Direct	Operation by Bluetooth: NO
Light distribution: Direct	Compatible with Apple HomeKit: NO
Material cover: Glass transparent	Compatible with Google Assistant: NO
Impact strength: IK08	Compatible with Amazon Alexa: NO
Nominal voltage: 220 ~ 240	Max. number of luminaires per miniature circuit breaker C16 (MCB): 18
Emergency power supply integrated: NO	Max. number of luminaires per miniature circuit breaker B16 (MCB): 11
Degree of protection (IP): IP66	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (t _q): 97.5 %
With light source: NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (t _q): 93 %
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (t _q): 78 %
Covering of the luminaire with thermally insulating material possible:	Failure rate at median useful life of 35,000 h at 25 °C ambient (t _q): 2 %
Suitable for number of light sources: 1	Failure rate at median useful life of 50,000 h at 25 °C ambient (t _q): 3 %
Suitable for built-in mounting: NO	Failure rate at median useful life of 100,000 h at 25 °C ambient (t _q): 6 %
With control gear: YES	Dimming DALI-2: NO
Suitable for workplace according to EN 12464-1:	Flickering value Pst LM: 1
Suitable for surface mounting: NO	Stroboscope effect value SVM: 0.4

Beam angle:	> 80° - Extreme wide beam	Colour of light adjustable:	No
Connectable conductor cross section:	0.75 ~ 2.5	Luminous flux adjustable:	No
Surface brushed:	NO	Beam angle adjustable:	No
Luminous flux in emergency mode:	-lm	Exchangeable control gear:	YES
Nominal current:	NA mA	Built-in diameter:	- mm
Colour temperature:	4000 K	Compatible with Casambi:	NO
Max. system power:	300 W	Energy efficiency class of the light source according to EU regulation 2019/2015:	NO
Rated luminous flux according to IEC 62722-2-1:	42000 lm	Luminous intensity:	NA cd
Colour of light:	White	Degree of protection (IP), rear side:	NA cd
Adjustability:	Swivelling	Movement sensor/presence detector technology:	NA cd
Suitable for traverse mounting:	YES	Luminaire efficacy:	NA cd
Suitable for pedestal/floor mounting:	YES	Rated luminous flux according to IEC 62722-2-1:	NA cd
Suitable for light-track mounting:	NO	Emergency power supply system:	NA cd
Suitable for clamp-mounting:	YES	Power consumption in emergency mode:	NA cd
Constant light output (CLO):	YES	Emergency function monitoring system:	NA cd
Built-in height:	NA mm	Containing product according to 2019/2020/EU:	NA cd
IFTTT support available:	NO	Total harmonic distortion (THD):	NA cd
Luminous flux:	- lm	Suitable for ceiling mounting:	YES
Type of wiring:	Suitable for loop-through wiring	Built-in length:	YES
Rated lifetime L70/B50 at 25 °C:	153135 h	Built-in height/depth:	-mm
Rated lifetime L80/B50 at 25 °C:	153135 h	Power factor:	0.9

PACKING_INFORMATION

WEIGHT	10.09 kg
WIDTH	130 mm
HEIGHT	660 mm
LENGTH	420 mm
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p>
STATISTICS	94054210