

PIR motion sensor 6m 800W IP65 Thorgeon



PIR motion sensor 6m 800W IP65 Thorgeon

ARTICLE_NUMBER: TH 02025

CHANGED_LAST: 30-01-2026

BRAND: Thorgeon

ETIM_GROUP: EG000013 - Domestic switching devices

ETIM_CLASS: EC000133 - Movement sensor/presence detector complete

SYNONYM: Auxiliary post, Movement sensor, Movement sensor / presence detector complete, Movement sensor complete, Movement sensor/presence detector complete, Multi-sensor, Presence detector



FEATURES

| | |
|--|--|
| Mounting method: Other | With signal unit: NO |
| Colour: White | Control current: -mA |
| Width: 55.4 mm | Teach-function for response value luminosity: NO |
| Model: Movement sensor | Networkable: NO |
| Halogen free: YES | Forced switch off: NO |
| Height: 36.8 mm | Scan angle: -° |
| Depth: 25.5 mm | Built-in length: -mm |
| Connection type: 25.5 mm | Impact strength: -mm |
| Surface protection: Untreated | With connection cable: NO |
| Creep-under protection: NO | Nominal voltage: 220 ~ 240 |
| Voltage type: AC | Degree of protection (IP): IP65 |
| Switch-on delay: -s | With alarm function: NO |
| Switch-off delay: -s | Transparent: NO |
| Built-in depth: -mm | Animal zone: NO |
| Frequency: 50 ~ 60 | Surface finishing: Matt |
| With remote control: NO | Detection angle horizontal: -° |
| Diameter: -mm | Min. switch-on time: 5 s |
| Suitable for wall mounting: NO | Max. duty cycle: 8 min |
| Built-in width: -mm | Response value luminosity adjustable: NO |
| Built-in diameter: -mm | Optimum mounting height: 1.8 m |
| Staircase light controller: NO | Pivoting range sensor, horizontal: -° |
| Bridging switch: NO | Pivoting range sensor, vertical: -° |
| Suitable for wireless transmission: NO | Number of switching zones: -° |
| Material quality: Thermoplastic | With DALI interface: NO |
| Max. reach frontally: 6 m | IFTTT support available: NO |
| Max. reach sideways: 6 m | Forced switch on: NO |
| Max. switching power: 800 W | Min. starting current: -A |
| Temperature: -20 ~ +40 | Min. depth of built-in installation box: -mm |
| Max. starting current: -A | Max. presence range: -m² |
| Material: Plastic | Compatible with Apple HomeKit: NO |
| Ambient temperature: NA °C | Compatible with Google Assistant: NO |
| Response value sensitivity adjustable: NO | Compatible with Amazon Alexa: NO |
| Connection cable length: -mm | Max. switching power LED: 800 W |
| Dim function with dimmer basic element: NO | Compatible with Casambi: NO |
| Response value luminosity: -lx | Background monitoring: NO |
| Suitable for C-load: NO | With acoustic sensor: NO |
| Diameter reach on floor: -m | Ceiling built-in mounting without installation box: NO |
| Remote operation: NO | Movement sensor/presence detector technology: NO |
| HVAC-control: NO | Sensor type: Passive infrared |
| Constant light control: NO | Suitable for ceiling mounting: NO |
| Substation input: NO | Anti-bacterial treatment: NO |

PACKING_INFORMATION

| | |
|--------|-------|
| WEIGHT | 64 gr |
| WIDTH | 48 mm |
| HEIGHT | 88 mm |
| LENGHT | 48 mm |

PACKING_CODE BX

PACKING_FORM Box
<p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p>

STATISTICS 85365003

