

LED E27 Fila DTW Ball G45x75 230V 420Lm 5W 920-927 AC Opal D



Article code:	L892745235
Last changed:	01-05-2026 09:06:10
Brand:	SPL,Schiefer
ETIM group:	EG000028 - Lamps
ETIM class:	EC001959 - LED-lamp/Multi-LED
Synonyms:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Specifications

Colour:	White	Lamp power:	5.000 W
Socket:	E27	Luminous flux:	378.000 ~ 462.000
Housing colour:	White	Colour consistency (McAdam ellipse):	SDCM6
Dimmable:	No	Total harmonic distortion:	SDCM6
Voltage type:	AC	Photobiological safety according to EN 62471:	RG0
With movement sensor:	No	Dimming phase cut-off (trailing edge):	Yes
With twilight switch:	No	Dimming phase cut-on (leading edge):	Yes
Colour rendering index CRI:	90-100	Dimming Touch and Dim:	No
With remote control:	No	Dimming Zigbee:	No
Diameter:	45 mm	No dim function:	No
Suitable for electronic ballast:	No	Lamp designation:	Other
Lamp efficacy:	84 lm/W	Filament lamp:	Yes
Luminous intensity:	-cd	Min. number of switching cycles:	50000
Lamp shape:	Round/globe	Beam angle:	360.000 °
Length:	75 mm	Rated luminous flux according to IEC 62612:	420 lm
Suitable for refrigerator:	No	Compatible with Apple HomeKit:	No
Remote operation possible:	No	Compatible with Google Assistant:	No
Nominal voltage:	220.000 ~ 240.000	Compatible with Amazon Alexa:	No
Degree of protection (IP):	IP20	Suitable for magnetic ballast:	No
Colour of light according to EN 12464-1:	Warm white < 3300 K	Energy efficiency class according to EU regulation 2019/2015:	G
Type of glass/cover:	Opal	Dimming Bluetooth:	No
Average nominal lifetime:	25000 h	Dimming Wi-Fi:	No
Nominal current:	21.000 ~ 23.000	Material of light bulb:	No
Colour temperature:	2000.000 ~ 2700.000	Total harmonic distortion (THD):	No
Weighted energy consumption in 1000 hours:	5 kWh	Power factor:	0.85

Packaging information

Weight	0.03 kg
Width	0.05 m
Height	0.09 m
Length	0.05 m
Packaging code <small>(according to EANCOM code list 7065)</small>	CT
Packaging form	Cardboard <small><p>A cardboard box or container</p></small>
CBS-code	85395200

