

Retrofit Puto led module 32W/40W/48W/55W 120° 4000K



Retrofit Puto led module 32W/40W/48W/55W 120° 4000K	
Article code:	PL 805852
Last changed:	06-05-2026 14:59:02
Brand:	Profolux
ETIM group:	EG000027 - Luminaires
ETIM class:	EC000109 - Batten luminaire
Synonyms:	Batten luminaire, Device carrier, Fluorescent batten, Wall luminaire



Specifications

Protection class according to IEC 61140:	--	Degree of protection (NEMA):	50000 h
Width:	65 mm	Filament test according to IEC 60695-2-11:	50000 h
Lamp holder:	None	Dimming 0-10 V:	No
Conductor cross section:	-mm ²	Dimming 1-10 V:	No
Connection type:	-mm ²	Dimming DALI:	No
Housing colour:	White	Dimming DMX:	No
Dimmable:	No	Dimming potentiometer (integrated):	No
Voltage type:	AC	Dimming LineSwitch:	No
With movement sensor:	No	Dimming manufacturer's proprietary system:	No
Suitable for lamp power:	- W	Dimming mains voltage modulation:	No
Type of control gear:	- W	Dimming phase cut-off (trailing edge):	No
Colour rendering index CRI:	80-89	Dimming phase cut-on (leading edge):	No
Diameter:	-mm	Dimming programmable:	No
With switch:	No	Dimming RF:	No
With light sensor:	No	Dimming Sine Wave Reduction:	No
Number of poles:	No	Dimming Touch and Dim:	No
Length:	1470 mm	Dimming Zigbee:	No
Height/depth:	-mm	Dimming with push-button:	No
Material:	Plastic	No dim function:	Yes
Lamp type:	LED not exchangeable	Light distributor:	Focal lens
With presence detector:	No	Luminaire efficacy:	-lm/W
Electrical connection with connector system:	No	Dimming DSI:	No
Suitable for emergency lighting:	No	Operation by Bluetooth:	No
Impact strength:	IK01	Compatible with Apple HomeKit:	No
Nominal voltage:	220 ~ 240	Compatible with Google Assistant:	No
Emergency power supply integrated:	No	Compatible with Amazon Alexa:	No
Degree of protection (IP):	IP20	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
With light source:	Yes	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No	Dimming DALI-2:	No
Covering of the luminaire with thermally insulating material possible:	No	Colour of light adjustable:	No
Suitable for number of light sources:	No	Luminous flux adjustable:	No
With control gear:	No	Beam angle adjustable:	No
Connectable conductor cross section:	- mm ²	Exchangeable control gear:	No
Luminous flux in emergency mode:	-lm	Compatible with Casambi:	No
Nominal current:	- mA	Energy efficiency class of the light source according to EU regulation 2019/2015:	D
Colour temperature:	4000 K	With lamp protection basket:	No
Max. system power:	-W	Movement sensor/presence detector technology:	No
Rated luminous flux according to IEC 62722-2-1:	-lm	Rated luminous flux according to IEC 62722-2-1:	No
Colour of light:	White	Emergency power supply system:	No
Constant light output (CLO):	No	Power consumption in emergency mode:	No
IFTTT support available:	No	Emergency function monitoring system:	No
Type of wiring:	No	Containing product according to 2019/2020/EU:	No
Rated lifetime L70/B50 at 25 °C:	50000 h	Power factor:	No

Packaging information

Weight	0 gr
Packaging code <small>(according to EANCOM code list 7065)</small>	BX
Packaging form	Box <small>-> A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</small></small>
CBS-code	94051040

