

Feelux DRIVER LED 30W 24V 6-WAY DISTRIBUTOR SMPS



24 V DC constant voltage LED driver (30 W), dimmable, for Feelux lighting systems.
Suitable for indoor use (IP20).

Article code: FL 363002

Last changed: 12-05-2026 16:23:32

Brand: Feelux

ETIM group: EG000030 - Accessories for lighting

ETIM class: EC002710 - LED driver

Synonyms: LED controlling, LED driver



Specifications

Protection class according to IEC 61140:	II	Dimming LineSwitch:	No
Width:	40 mm	Dimming manufacturer's proprietary system:	Yes
Model:	Static	Dimming mains voltage modulation:	No
Height:	30 mm	Dimming phase cut-off (trailing edge):	No
Dimmable:	Yes	Dimming phase cut-on (leading edge):	No
Housing:	Plastic housing	Dimming programmable:	No
Power consumption:	30 W	Dimming RF:	No
Diameter:	-mm	Dimming Sine Wave Reduction:	No
Length:	150 mm	Dimming Touch and Dim:	No
Ambient temperature:	-20 ~ 50	Dimming Zigbee:	No
Suitable for outdoor use:	No	Dimming with push-button:	No
Short-circuit protected:	Yes	No dim function:	No
Input voltage:	100 ~ 240	Dimming DSI:	No
Output voltage:	24 V	Operation by Bluetooth:	No
Output power:	30 W	PWM modulation:	No
Degree of protection (IP):	IP20	Compatible with Apple HomeKit:	No
Output current:	1250 mA	Compatible with Google Assistant:	No
Frequency input voltage:	50 ~ 60	Compatible with Amazon Alexa:	No
Overload protection:	No	Max. number of luminaires per miniature circuit breaker C16 (MCB):	No
Overtemperature protection:	Yes	Max. number of luminaires per miniature circuit breaker B16 (MCB):	No
Suitable for constant current:	No	Dimming DALI-2:	No
Suitable for constant voltage:	Yes	Compatible with Casambi:	No
Suitable for DC-voltage (primary side):	Yes	Dimming D4i:	No
Constant light output (CLO):	No	Emergency power supply system:	No
Number of colour channels:	No	Mains surge immunity (differential mode, L-N):	No
IFTTT support available:	No	Mains surge immunity (common mode, L/N-Ground):	No
Dimming 0-10 V:	No	Driver lifetime:	No
Dimming 1-10 V:	No	DIN-rail mounting:	No
Dimming DALI:	No	Independently operating:	No
Dimming DMX:	No	Efficiency:	-%
Dimming potentiometer (integrated):	No	Operation by Matter:	-%

Packaging information

Weight	0 gr
Packaging code <small>(according to EANCOM code list 7065)</small>	BX
Packaging form	Box <small><p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p></small>

