

Single led Bi-pin T1 3/4 24V WHITE DC



Schiefer has, for the replacement of signaling lamps, an extensive program in LED signaling. These are often used for push buttons, signal lighting, and all machines and places where small lamps are used.

Article code: 001328030

Last changed: 05-06-2026 12:33:07

Brand: SPL,Schiefer

ETIM group: EG000028 - Lamps

ETIM class: EC000399 - Indication- and signalling lamp

Synonyms: Incandescent lamp, Indication- and signalling lamp, Lamp, Traffic signalling lamp



Specifications

Nominal current:	10 mA	Suitable for pointer:	No
Colour:	White	Halogen:	No
Socket:	Bi-pin	Technology:	LED
Luminous flux:	4 lm	Xenon:	No
Colour temperature:	6500 K	Average nominal lifetime:	25000 h
Total length:	16 mm	Lamp voltage:	24.000 V
Diameter:	6 mm	Lamp power:	0.240 W
Lamp shape:	Tube, single-ended	Suitable for round flashing luminaire:	No
Krypton:	No	Energy efficiency class according to EU regulation 2019/2015:	No

Packaging information

Weight	0 kg
Width	0.01 m
Height	0.02 m
Length	0.01 m
Packaging code <small>(according to EANCOM code list 7065)</small>	NE
Packaging form	Not packed <small>-p>The item is without packaging or & quot; unpacked & quot; delivered.</p></small>
CBS-code	85395200

