

LED GU10 MR16 50x56 24-30V 315Lm 5W 827 38° DC Non-Dim



Article code:	L641704027
Last changed:	15-07-2026 09:14:54
Brand:	SPL,Schiefer
ETIM group:	EG000028 - Lamps
ETIM class:	EC001959 - LED-lamp/Multi-LED
Synonyms:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Specifications

Colour:	White	Lamp power:	5 W
Socket:	GU10	Luminous flux:	284 ~ 347
Housing colour:	Grey	Colour consistency (McAdam ellipse):	SDCM6
Dimmable:	No	Total harmonic distortion:	SDCM6
Voltage type:	DC	Photobiological safety according to EN 62471:	RG0
With movement sensor:	No	Dimming phase cut-off (trailing edge):	No
With twilight switch:	No	Dimming phase cut-on (leading edge):	No
Colour rendering index CRI:	80-89	Dimming Touch and Dim:	No
With remote control:	No	Dimming Zigbee:	No
Diameter:	50 mm	No dim function:	Yes
Suitable for electronic ballast:	Yes	Lamp designation:	MR16
Lamp efficacy:	63 lm/W	Filament lamp:	No
Luminous intensity:	461 cd	Min. number of switching cycles:	12500
Lamp shape:	Reflector	Beam angle:	38.000 °
Length:	56 mm	Rated luminous flux according to IEC 62612:	315 lm
Suitable for refrigerator:	No	Compatible with Apple HomeKit:	No
Remote operation possible:	No	Compatible with Google Assistant:	No
Nominal voltage:	24 ~ 30	Compatible with Amazon Alexa:	No
Degree of protection (IP):	IP20	Suitable for magnetic ballast:	No
Colour of light according to EN 12464-1:	Warm white < 3300 K	Energy efficiency class according to EU regulation 2019/2015:	G
Type of glass/cover:	Clear	Dimming Bluetooth:	No
Average nominal lifetime:	25000 h	Dimming Wi-Fi:	No
Nominal current:	167 ~ 208	Material of light bulb:	No
Colour temperature:	2700.000 K	Total harmonic distortion (THD):	No
Weighted energy consumption in 1000 hours:	5 kWh	Power factor:	0.5

Packaging information

Weight	0.04 kg
Width	0.05 m
Height	0.06 m
Length	0.05 m
Packaging code (according to EANCOM code list 7065)	CT
Packaging form	Cardboard A cardboard box or container
CBS-code	85395200

