

LED Lamp CorePro LED PLC 5.9W 840 2P G24d-1



Article code:	PH 287525
Last changed:	05-08-2026 07:23:19
Brand:	PHILIPS
ETIM group:	EG000028 - Lamps
ETIM class:	EC001959 - LED-lamp/Multi-LED
Synonyms:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Specifications

Colour:	White	Lamp power:	5.900 W
Socket:	G24d-1	Luminous flux:	660.000 lm
Housing colour:	White	Colour consistency (McAdam ellipse):	SDCM6
Dimmable:	No	Total harmonic distortion:	0.15
Voltage type:	AC	Photobiological safety according to EN 62471:	RG1
With movement sensor:	No	Dimming phase cut-off (trailing edge):	No
With twilight switch:	No	Dimming phase cut-on (leading edge):	No
Colour rendering index CRI:	80-89	Dimming Touch and Dim:	No
With remote control:	No	Dimming Zigbee:	No
Diameter:	34 mm	No dim function:	Yes
Suitable for electronic ballast:	No	Lamp designation:	Other
Lamp efficacy:	111 lm/W	Filament lamp:	No
Luminous intensity:	-cd	Min. number of switching cycles:	50000
Lamp shape:	Tube, single-ended	Beam angle:	120.000 °
Length:	138 mm	Rated luminous flux according to IEC 62612:	660 lm
Suitable for refrigerator:	No	Compatible with Apple HomeKit:	No
Remote operation possible:	No	Compatible with Google Assistant:	No
Nominal voltage:	220.000 ~ 240.000	Compatible with Amazon Alexa:	No
Degree of protection (IP):	IP20	Suitable for magnetic ballast:	Yes
Colour of light according to EN 12464-1:	Neutral white 3300-5300 K	Energy efficiency class according to EU regulation 2019/2015:	E
Type of glass/cover:	Frosted	Dimming Bluetooth:	No
Average nominal lifetime:	30000 h	Dimming Wi-Fi:	No
Nominal current:	31.000 mA	Material of light bulb:	Plastic
Colour temperature:	4000.000 K	Total harmonic distortion (THD):	15 %
Weighted energy consumption in 1000 hours:	6 kWh	Power factor:	0.9

Packaging information

Weight	0.09 kg
Width	0.03 m
Height	0.14 m
Length	0.03 m
Packaging code (according to EANCOM code list 7065)	BME
Packaging form	Blister packaging A type of packaging where the item is packed between a preformed & quot; bubble & quot; (usually from transparent plastic) and a cardboard & quot; carrier & quot;. These can be attached to each other by stapling, heat axes, gluing or otherwise. In some cases, the blister package is folded around the product like an oyster shell. Blister packaging is usually made by means of thermo formation of polyvinyl chloride, but almost any thermoplast can be formed into a bubble.
CBS-code	85395200





