


PIR Motion Sensor DALI 8m IP54 Anthracite Thorgeon



PIR Motion Sensor DALI 8m IP54 Anthracite Thorgeon	
Article code:	TH 02034
Last changed:	11-08-2026 13:13:35
Brand:	Thorgeon
ETIM group:	EG000013 - Domestic switching devices
ETIM class:	EC000133 - Movement sensor/presence detector complete
Synonyms:	Auxiliary post, Movement sensor, Movement sensor / presence detector complete, Movement sensor complete, Movement sensor/presence detector complete, Multi-sensor, Presence detector



Specifications

Mounting method:	Other	With signal unit:	No
Colour:	Anthracite	Control current:	-mA
Width:	102 mm	Teach-function for response value luminosity:	No
Model:	Movement sensor	Networkable:	No
Halogen free:	Yes	Forced switch off:	No
Height:	102 mm	Scan angle:	360 °
Depth:	51.7 mm	Built-in length:	-mm
Connection type:	Other	Impact strength:	-mm
Surface protection:	Untreated	With connection cable:	No
Creep-under protection:	No	Nominal voltage:	220 ~ 240
Voltage type:	AC	Degree of protection (IP):	IP54
Switch-on delay:	-s	With alarm function:	No
Switch-off delay:	-s	Transparent:	No
Built-in depth:	-mm	Animal zone:	No
Frequency:	- Hz	Surface finishing:	Matt
With remote control:	Yes	Detection angle horizontal:	- °
Diameter:	-mm	Min. switch-on time:	10 s
Suitable for wall mounting:	No	Max. duty cycle:	60 min
Built-in width:	-mm	Response value luminosity adjustable:	No
Built-in diameter:	-mm	Optimum mounting height:	2.2 m
Staircase light controller:	No	Swivel range sensor, horizontal:	- °
Bridging switch:	No	Swivel range sensor, vertical:	- °
Suitable for wireless transmission:	No	Number of switching zones:	- °
Material quality:	Thermoplastic	With DALI interface:	Yes
Max. reach frontally:	8 m	IFTTT support available:	No
Max. reach sideways:	-m	Forced switch on:	No
Max. switching power:	-W	Min. starting current:	-A
Temperature:	-20 ~ 40	Min. depth of built-in installation box:	-mm
Max. starting current:	-A	Max. presence range:	-m²
Material:	Plastic	Compatible with Apple HomeKit:	No
Ambient temperature:	- °C	Compatible with Google Assistant:	No
Response value sensitivity adjustable:	Yes	Compatible with Amazon Alexa:	No
Connection cable length:	-mm	Max. switching power LED:	2000 W
Dim function with dimmer basic element:	No	Compatible with Casambi:	No
Response value luminosity:	10 ~ 2000	Background monitoring:	No
Suitable for C-load:	No	With acoustic sensor:	No
Diameter reach on floor:	6 m	Ceiling built-in mounting without installation box:	No
Remote operation:	No	Movement sensor/presence detector technology:	No
HVAC-control:	No	Sensor type:	Passive infrared
Constant light control:	Yes	Suitable for ceiling mounting:	Yes
Substation input:	No	Anti-bacterial treatment:	No

Packaging information

Weight	0 gr
Width	109 mm
Height	124 mm
Length	89 mm

Packaging code BX
(according to EANCOM code list 7065)

Packaging form Box
<p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p>

