

Cable Trunking with Rem. Cover 2m 60X40 THORGEON



Cable Trunking with Rem. Cover 2m 60X40 THORGEON	
Article code:	TH 15239
Last changed:	11-08-2026 15:22:17
Brand:	Thorgeon
ETIM group:	EG000004 - Cable carrying systems
ETIM class:	EC000047 - Cable tray
Synonyms:	Cable duct, Cable support system, Cable tray, Cable tray/wide span cable tray, Cable trough, Ceiling cable tray, Ceiling cable tray system, Connector, Luminaire carrier tray



Specifications

Colour:	Yellow	Suitable for circuit integrity:	No
Width:	60 mm	With cover:	Yes
Model:	Without connector	Load test type according to IEC 61537:	Yes
Height:	40 mm	Possible support spacing:	NA m
Type of connection:	40 mm	Safe working load according to IEC 61537 with support spacing 0.5 m:	-N/m
RAL-number:	9010	Safe working load according to IEC 61537 with support spacing 1.0 m:	-N/m
Surface protection:	Other	Safe working load according to IEC 61537 with support spacing 1.5 m:	-N/m
Connector design:	Other	Safe working load according to IEC 61537 with support spacing 2.0 m:	-N/m
Weight:	-kg/m	Safe working load according to IEC 61537 with support spacing 2.5 m:	-N/m
Material thickness:	-mm	Safe working load according to IEC 61537 with support spacing 3.0 m:	-N/m
Side perforation:	No	Safe working load according to IEC 61537 with support spacing 4.0 m:	-N/m
Material quality:	Polyvinyl chloride (PVC)	Safe working load according to IEC 61537 with support spacing 5.0 m:	-N/m
Length:	2000 mm	Safe working load according to IEC 61537 with support spacing 6.0 m:	-N/m
Working temperature:	NA °C	Safe working load according to IEC 61537 with support spacing 7.0 m:	-N/m
Material:	Plastic	Safe working load according to IEC 61537 with support spacing 8.0 m:	-N/m
Bottom perforation:	Yes	Safe working load according to IEC 61537 with support spacing 10.0 m:	-N/m
Usable cross section:	-mm ²	Safe working load according to IEC 61537 with support spacing 9.0 m:	-N/m
NATO-mounting holes:	No	Safe working load according to IEC 61537 with support spacing 11.0 m:	-N/m
Working length:	-mm	Safe working load according to IEC 61537 with support spacing 12.0 m:	-N/m

Packaging information

Weight	0 gr
Packaging code (according to EANCOM code list 7065)	BX
Packaging form	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product
CBS-code	73089098

