

## Twilight sensor 300W IP65 Thorgeon



|                                    |                                       |
|------------------------------------|---------------------------------------|
| Twilight sensor 300W IP65 Thorgeon |                                       |
| Article code:                      | TH 02018                              |
| Last changed:                      | 11-08-2026 15:47:18                   |
| Brand:                             | Thorgeon                              |
| ETIM group:                        | EG000013 - Domestic switching devices |
| ETIM class:                        | EC000189 - Twilight switch            |
| Synonyms:                          | Twilight switch                       |



## Specifications

|                                          |       |                                          |                       |
|------------------------------------------|-------|------------------------------------------|-----------------------|
| Nominal voltage:                         | 220 V | Operating temperature:                   | - °C                  |
| Mounting method:                         | 220 V | Switching-off brightness:                | - lx                  |
| Colour:                                  | 220 V | Suitable for C-load:                     | No                    |
| Width:                                   | 48 mm | Engaging brightness:                     | 3 ~ 2000              |
| Halogen free:                            | No    | RAL-number (similar):                    | 3 ~ 2000              |
| Contacts:                                | No    | Type of sensor:                          | Built-in light sensor |
| Height:                                  | 64 mm | Transparent:                             | No                    |
| Depth:                                   | 27 mm | Surface finishing:                       | No                    |
| Surface protection:                      | 27 mm | Suitable for degree of protection (IP):  | IP65                  |
| Switch-on delay:                         | -s    | With automatic night switch-off:         | No                    |
| Switch-off delay:                        | -s    | With DALI interface:                     | No                    |
| Swivelling:                              | No    | IFTTT support available:                 | No                    |
| Diameter:                                | -mm   | Min. depth of built-in installation box: | -mm                   |
| Material quality:                        | -mm   | Compatible with Apple HomeKit:           | No                    |
| Max. switching current (resistive load): | 15 A  | Compatible with Google Assistant:        | No                    |
| Max. switching power:                    | -W    | Compatible with Amazon Alexa:            | No                    |
| Working temperature:                     | - °C  | Max. switching power LED:                | 300 W                 |

## Packaging information

|                                                        |                                                                                                                                                                                                                                                                                            |
|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                                                 | 1.76 gr                                                                                                                                                                                                                                                                                    |
| Width                                                  | 60 mm                                                                                                                                                                                                                                                                                      |
| Height                                                 | 80 mm                                                                                                                                                                                                                                                                                      |
| Length                                                 | 69 mm                                                                                                                                                                                                                                                                                      |
| Packaging code<br>(according to EANCOM code list 7065) | BX                                                                                                                                                                                                                                                                                         |
| Packaging form                                         | Box<br><p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p> |
| CBS-code                                               | 85365003                                                                                                                                                                                                                                                                                   |

