

Philips BVP130 LED260-4S/740 26000Lm IP66



Philips BVP130 LED260-4S/740 26000Lm IP66	
Article code:	PH 096397
Last changed:	20-08-2026 11:02:07
Brand:	PHILIPS
ETIM group:	EG000027 - Luminaires
ETIM class:	EC001744 - Downlight/spot/floodlight
Synonyms:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight



Specifications

Protection class according to IEC 61140:	I	Built-in width:	389 mm
Width:	422 mm	Colour consistency (McAdam ellipse):	SDCM3
Outer diameter:	-mm	Total harmonic distortion:	6
Reflector:	None	Photobiological safety according to EN 62471:	RG1
Lamp holder:	None	Degree of protection (NEMA):	RG1
Conductor cross section:	1.5 mm²	Rated ambient temperature according to IEC 62722-2-1:	- °C
Connection type:	Insulation displacement connector	Filament test according to IEC 60695-2-11:	650 °C - 30 s
Housing colour:	Grey	Dimming 0-10 V:	No
Dimmable:	No	Dimming 1-10 V:	No
Surface protection:	Powder coating	Dimming DALI:	No
Voltage type:	AC	Dimming DMX:	No
With movement sensor:	No	Dimming potentiometer (integrated):	No
Suitable for lamp power:	- W	Dimming LineSwitch:	No
Type of control gear:	LED operating device current-controlled	Dimming manufacturer's proprietary system:	No
Colour rendering index CRI:	70-79	Dimming mains voltage modulation:	No
Suitable for wall mounting:	Yes	Dimming phase cut-off (trailing edge):	No
Built-in width:	389 mm	Dimming phase cut-on (leading edge):	No
With light sensor:	No	Dimming programmable:	No
Suitable for suspended mounting:	No	Dimming RF:	No
Luminous intensity:	20827 cd	Dimming Sine Wave Reduction:	No
Number of poles:	3	Dimming Touch and Dim:	No
Length:	340.5 mm	Dimming Zigbee:	No
Height/depth:	67.4 mm	Dimming with push-button:	No
Housing material:	Aluminium	No dim function:	Yes
Lamp type:	LED not exchangeable	Light distributor:	Diffuser lens/optic/panel
Reflector colour:	LED not exchangeable	Luminaire efficacy:	143 lm/W
With presence detector:	No	Suitable for low voltage cable system:	No
Degree of protection (IP), front side:	IP66	Dimming DSI:	No
Built-in length:	486 mm	Unified Glare Ratio (UGR):	No
Light outlet:	Direct	Operation by Bluetooth:	No
Light distribution:	Asymmetric	Compatible with Apple HomeKit:	No
Material cover:	Glass transparent	Compatible with Google Assistant:	No
Impact strength:	IK08	Compatible with Amazon Alexa:	No
Nominal voltage:	220 ~ 240	Max. number of luminaires per miniature circuit breaker C16 (MCB):	13
Emergency power supply integrated:	No	Max. number of luminaires per miniature circuit breaker B16 (MCB):	8
Degree of protection (IP):	IP66	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	-%
With light source:	Yes	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	90 %
Covering of the luminaire with thermally insulating material possible:	No	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Suitable for number of light sources:	80	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Suitable for built-in mounting:	No	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	10 %
With control gear:	Yes	Dimming DALI-2:	No
Suitable for workplace according to EN 12464-1:	Yes	Flickering value Pst LM:	0.2
Suitable for surface mounting:	Yes	Stroboscope effect value SVM:	0.07

Beam angle:	41-80° - Wide beam	Colour of light adjustable:	No
Connectable conductor cross section:	7 ~ 14	Luminous flux adjustable:	No
Surface brushed:	Yes	Beam angle adjustable:	No
Luminous flux in emergency mode:	-lm	Exchangeable control gear:	Yes
Nominal current:	966 mA	Built-in diameter:	- mm
Colour temperature:	4000 K	Compatible with Casambi:	No
Max. system power:	182 W	Energy efficiency class of the light source according to EU regulation 2019/2015:	D
Rated luminous flux according to IEC 62722-2-1:	260000 lm	Luminous intensity:	20827 cd
Colour of light:	White	Degree of protection (IP), rear side:	IP66
Adjustability:	Swivelling	Movement sensor/presence detector technology:	IP66
Suitable for traverse mounting:	Yes	Luminaire efficacy:	IP66
Suitable for pedestal/floor mounting:	Yes	Rated luminous flux according to IEC 62722-2-1:	IP66
Suitable for light-track mounting:	No	Emergency power supply system:	IP66
Suitable for clamp-mounting:	No	Power consumption in emergency mode:	IP66
Constant light output (CLO):	No	Emergency function monitoring system:	IP66
Built-in height:	64 mm	Containing product according to 2019/2020/EU:	IP66
IFTTT support available:	No	Total harmonic distortion (THD):	IP66
Luminous flux:	26000 lm	Suitable for ceiling mounting:	No
Type of wiring:	Ending	Built-in length:	No
Rated lifetime L70/B50 at 25 °C:	70000 h	Built-in height/depth:	64 mm
Rated lifetime L80/B50 at 25 °C:	70000 h	Power factor:	0.99

Packaging information

Weight	0 gr
Packaging code (according to EANCOM code list 7065)	BX
Packaging form	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product

