



Specifications

Protection class according to IEC 61140:	--	Colour consistency (McAdam ellipse):	50000 h
Width:	595 mm	Total harmonic distortion:	50000 h
Outer diameter:	-mm	Photobiological safety according to EN 62471:	50000 h
Lamp holder:	-mm	Degree of protection (NEMA):	50000 h
Conductor cross section:	-mm ²	Rated ambient temperature according to IEC 62722-2-1:	- °C
Connection type:	-mm ²	Filament test according to IEC 60695-2-11:	- °C
Housing colour:	White	Dimming 0-10 V:	No
Dimmable:	No	Dimming 1-10 V:	No
With connection cord and plug:	No	Dimming DALI:	No
Voltage type:	AC	Dimming DMX:	No
With movement sensor:	No	Dimming potentiometer (integrated):	No
Suitable for lamp power:	45 W	Dimming LineSwitch:	No
Type of grid:	45 W	Dimming manufacturer's proprietary system:	No
Length of power cord:	-mm	Dimming mains voltage modulation:	No
Type of control gear:	-mm	Dimming phase cut-off (trailing edge):	No
Colour rendering index CRI:	80-89	Dimming phase cut-on (leading edge):	No
Suitable for wall mounting:	No	Dimming programmable:	No
Built-in width:	595 mm	Dimming RF:	No
Built-in diameter:	-mm	Dimming Sine Wave Reduction:	No
With switch:	No	Dimming Touch and Dim:	No
With light sensor:	No	Dimming Zigbee:	No
Suitable for suspended mounting:	No	Dimming with push-button:	No
Luminous intensity:	-cd	No dim function:	Yes
Number of poles:	-cd	Light distributor:	Yes
Length:	1195 mm	Luminaire efficacy:	117 lm/W
Height/depth:	40 mm	Dimming DSI:	No
Housing material:	Aluminium	Unified Glare Ratio (UGR):	21
Lamp type:	LED not exchangeable	Operation by Bluetooth:	No
With presence detector:	No	Compatible with Apple HomeKit:	No
Degree of protection (IP), front side:	No	Compatible with Google Assistant:	No
Built-in length:	1195 mm	Compatible with Amazon Alexa:	No
Suitable for light line configuration:	No	Max. number of luminaires per miniature circuit breaker C16 (MCB):	No
Suitable for emergency lighting:	No	Max. number of luminaires per miniature circuit breaker B16 (MCB):	No
Light outlet:	No	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Light distribution:	No	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Material cover:	Plastic, opal	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	-%
Impact strength:	IK06	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Nominal voltage:	220 ~ 250	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Emergency power supply integrated:	No	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	-%
Degree of protection (IP):	IP22	Dimming DALI-2:	No
With light source:	Yes	Flickering value Pst LM:	No
With mounting material:	No	Stroboscope effect value SVM:	No
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No	Colour of light adjustable:	Positions
Covering of the luminaire with thermally insulating material possible:	No	Luminous flux adjustable:	No

Suitable for number of light sources:	No	Beam angle adjustable:	No
Suitable for built-in mounting:	Yes	Exchangeable control gear:	No
With control gear:	Yes	Compatible with Casambi:	No
Suitable for workplace according to EN 12464-1:	No	Energy efficiency class of the light source according to EU regulation 2019/2015:	E
Suitable for surface mounting:	Yes	Luminous intensity:	- cd
Beam angle:	Open beam/diffuse	Degree of protection (IP), rear side:	- cd
Connectable conductor cross section:	- mm ²	Movement sensor/presence detector technology:	- cd
Luminous flux in emergency mode:	5260 lm	Luminaire efficacy:	- cd
Nominal current:	- mA	Rated luminous flux according to IEC 62722-2-1:	- cd
Colour temperature:	3000 ~ 5000	Emergency power supply system:	- cd
Max. system power:	45 W	Power consumption in emergency mode:	- cd
Rated luminous flux according to IEC 62722-2-1:	5260 lm	Emergency function monitoring system:	- cd
Colour of light:	Multi-coloured	Containing product according to 2019/2020/EU:	- cd
With air slots:	No	Total harmonic distortion (THD):	- cd
Suitable for clamp-mounting:	No	Max. number of luminaires per miniature circuit breaker C10 (MCB):	- cd
Constant light output (CLO):	No	Suitable for ceiling mounting:	Yes
IFTTT support available:	No	Built-in height/depth:	40 mm
Type of wiring:	No	Surface protection housing:	40 mm
Rated lifetime L70/B50 at 25 °C:	50000 h	Power factor:	0.95
Rated lifetime L80/B50 at 25 °C:	50000 h	Meets min. EIA service life criterion L90 (at 50,000 hours at tq = 25°C):	No

Packaging information

Weight	0 gr
Packaging code (according to EANCOM code list 7065)	BX
Packaging form	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product

