


Inbouwspot - Wit - QR-C 51 / MR16 - Max 50 Watt Deluna



ARTICLE_NUMBER: 85007602

CHANGED_LAST: 13-12-2024

BRAND: Vezalux

ETIM_GROUP: EG000027 - Luminaires

ETIM_CLASS: EC002892 - Ceiling-/wall luminaire

SYNONYM: Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire



FEATURES

Width:	83 mm	Rated ambient temperature according to IEC 62722-2-1:	NA/NA °C
Outer diameter:	83 mm	Dimming 0-10 V:	NO
Lamp holder:	GU5.3	Dimming 1-10 V:	NO
Conductor cross section:	0 mm²	Dimming DALI:	NO
Housing colour:	White	Dimming DMX:	NO
With movement sensor:	NO	Dimming potentiometer (integrated):	NO
Suitable for lamp power:	NA/NA W	Dimming LineSwitch:	NO
Built-in width:	0 mm	Dimming manufacturer's proprietary system:	NO
Built-in diameter:	68 mm	Dimming mains voltage modulation:	NO
With light sensor:	NO	Dimming phase cut-off (trailing edge):	NO
Suitable for suspended mounting:	NO	Dimming phase cut-on (leading edge):	NO
Luminous intensity:	0 cd	Dimming programmable:	NO
Length:	0 mm	Dimming RF:	NO
Height/depth:	130 mm	Dimming Sine Wave Reduction:	NO
Housing material:	Aluminium	Dimming Touch and Dim:	NO
Built-in length:	0 mm	Dimming Zigbee:	NO
Suitable for light line configuration:	NO	Dimming with push-button:	NO
Suitable for emergency lighting:	NO	No dim function:	NO
Nominal voltage:	NA/NA V	Luminaire efficacy:	0 lm/W
Emergency power supply integrated:	NO	Dimming DSI:	NO
With light source:	NO	Operation by Bluetooth:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Compatible with Apple HomeKit:	NO
Covering of the luminaire with thermally insulating material possible:	NO	Compatible with Google Assistant:	NO
Suitable for built-in mounting:	NO	Compatible with Amazon Alexa:	NO
With control gear:	NO	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for workplace according to EN 12464-1:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for surface mounting:	NO	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Nominal current:	NA/NA mA	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Colour temperature:	NA/NA K	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Max. system power:	0 W	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Rated luminous flux according to IEC 62722-2-1:	0 lm	Dimming DALI-2:	NO
With air slots:	NO	Exchangeable control gear:	NO
Constant light output (CLO):	NO	Suitable for ceiling mounting:	NO
IFTTT support available:	NO	Built-in height/depth:	0 mm
Rated lifetime L70/B50 at 25 °C:	0 h		

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box

A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product.
