


Elba pendel ball brass + G125 POR



ARTICLE_NUMBER: 810075.00A

CHANGED_LAST: 23-05-2025

BRAND: Daylight Italia

ETIM_GROUP: EG000027 - Luminaires

ETIM_CLASS: EC001743 - Pendant luminaire

SYNONYM: Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire



FEATURES

Width:	0 mm	Rated lifetime L70/B50 at 25 °C:	15000 h
Reflector:	None	Dimming 0-10 V:	NO
Lamp holder:	E27	Dimming 1-10 V:	NO
Conductor cross section:	0 mm²	Dimming DALI:	NO
Housing colour:	Gold	Dimming DMX:	NO
Suitable for lamp power:	NA/NA W	Dimming potentiometer (integrated):	NO
Type of control gear:	Not required	Dimming LineSwitch:	NO
Colour rendering index CRI:	90-100	Dimming manufacturer's proprietary system:	NO
Diameter:	125 mm	Dimming mains voltage modulation:	NO
Length:	178 mm	Dimming phase cut-off (trailing edge):	NO
Height/depth:	0 mm	Dimming phase cut-on (leading edge):	NO
Housing material:	Plastic	Dimming programmable:	NO
Lamp type:	LED exchangeable	Dimming RF:	NO
Direct-/indirect proportion separately controllable:	NO	Dimming Sine Wave Reduction:	NO
Suitable for light line configuration:	NO	Dimming Touch and Dim:	NO
Suitable for emergency lighting:	NO	Dimming Zigbee:	NO
Light outlet:	Direct	Dimming with push-button:	NO
Pendant length:	1500/1500 mm	No dim function:	NO
Nominal voltage:	220/240 V	Light distributor:	None
Emergency power supply integrated:	NO	Luminaire efficacy:	0 lm/W
Degree of protection (IP):	IP20	Dimming DSI:	NO
With light source:	NO	Compatible with Apple HomeKit:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Compatible with Google Assistant:	NO
Suitable for number of light sources:	1	Compatible with Amazon Alexa:	NO
With control gear:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With suspension:	NO	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for workplace according to EN 12464-1:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Nominal current:	NA/NA mA	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Colour temperature:	2700/2700 K	Dimming DALI-2:	NO
Max. system power:	0 W	Colour of light adjustable:	No
Rated luminous flux according to IEC 62722-2-1:	0 lm	Luminous flux adjustable:	No
Colour of light:	White	Beam angle adjustable:	No
Constant light output (CLO):	NO	Exchangeable control gear:	NO
IFTTT support available:	NO		

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box

A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product.

STATISTICS 94051041

PAGE 3/4

PAGE 3/4

IBAN NL65 INGB 0008 3845 00
BIC INGBNL2A

BTW NL857194811B01
KVK 67841333

All transactions with Vezalux are subject to our general terms of trading
as declared with the Chamber of Commerce at Breda 67841333.



