

## Elba pendel ball white + G125 Milk



ARTICLE\_NUMBER: 810088.00A

CHANGED\_LAST: 23-05-2025

BRAND: Daylight Italia

ETIM\_GROUP: EG000027 - Luminaires

ETIM\_CLASS: EC001743 - Pendant luminaire

SYNONYM: Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire



## FEATURES

Width:	0 mm	Rated lifetime L70/B50 at 25 °C:	15000 h
Reflector:	None	Dimming 0-10 V:	NO
Lamp holder:	E27	Dimming 1-10 V:	NO
Conductor cross section:	0 mm²	Dimming DALI:	NO
Housing colour:	White	Dimming DMX:	NO
Suitable for lamp power:	NA/NA W	Dimming potentiometer (integrated):	NO
Type of control gear:	Not required	Dimming LineSwitch:	NO
Colour rendering index CRI:	90-100	Dimming manufacturer's proprietary system:	NO
Diameter:	125 mm	Dimming mains voltage modulation:	NO
Length:	175 mm	Dimming phase cut-off (trailing edge):	NO
Height/depth:	0 mm	Dimming phase cut-on (leading edge):	NO
Housing material:	Plastic	Dimming programmable:	NO
Lamp type:	LED exchangeable	Dimming RF:	NO
Direct-/indirect proportion separately controllable:	NO	Dimming Sine Wave Reduction:	NO
Suitable for light line configuration:	NO	Dimming Touch and Dim:	NO
Suitable for emergency lighting:	NO	Dimming Zigbee:	NO
Light outlet:	Direct	Dimming with push-button:	NO
Pendant length:	1500/1500 mm	No dim function:	NO
Nominal voltage:	220/240 V	Light distributor:	None
Emergency power supply integrated:	NO	Luminaire efficacy:	0 lm/W
Degree of protection (IP):	IP20	Dimming DSI:	NO
With light source:	NO	Compatible with Apple HomeKit:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Compatible with Google Assistant:	NO
Suitable for number of light sources:	1	Compatible with Amazon Alexa:	NO
With control gear:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With suspension:	NO	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for workplace according to EN 12464-1:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Nominal current:	NA/NA mA	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Colour temperature:	2700/2700 K	Dimming DALI-2:	NO
Max. system power:	0 W	Colour of light adjustable:	No
Rated luminous flux according to IEC 62722-2-1:	0 lm	Luminous flux adjustable:	No
Colour of light:	White	Beam angle adjustable:	No
Constant light output (CLO):	NO	Exchangeable control gear:	NO
IFTTT support available:	NO		

## PACKING\_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box

A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product.

---

STATISTICS 94051041

---

PAGE 3/4

PAGE 3/4

**IBAN** NL65 INGB 0008 3845 00  
**BIC** INGBNL2A

**BTW** NL857194811B01  
**KVK** 67841333

All transactions with Vezalux are subject to our general terms of trading  
as declared with the Chamber of Commerce at Breda 67841333.



