

Elba pendel kit ball black + rosette black + 1,5m black cable



ARTICLE_NUMBER:	800020.00A
CHANGED_LAST:	23-05-2025
BRAND:	Daylight Italia
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001743 - Pendant luminaire
SYNONYM:	Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire



FEATURES

Width:	80 mm	Constant light output (CLO):	NO
Reflector:	None	IFTTT support available:	NO
Lamp holder:	E27	Rated lifetime L70/B50 at 25 °C:	0 h
Conductor cross section:	0 mm²	Dimming 0-10 V:	NO
Connection type:	Push-in clamp	Dimming 1-10 V:	NO
Housing colour:	Black	Dimming DALI:	NO
Suitable for lamp power:	NA/NA W	Dimming DMX:	NO
Type of grid:	High-gloss	Dimming potentiometer (integrated):	NO
Type of control gear:	Not required	Dimming LineSwitch:	NO
Diameter:	80 mm	Dimming manufacturer's proprietary system:	NO
Length:	1500 mm	Dimming mains voltage modulation:	NO
Height/depth:	80 mm	Dimming phase cut-off (trailing edge):	NO
Housing material:	Plastic	Dimming phase cut-on (leading edge):	NO
Lamp type:	LED exchangeable	Dimming programmable:	NO
Direct-/indirect proportion separately controllable:	NO	Dimming RF:	NO
Suitable for light line configuration:	NO	Dimming Sine Wave Reduction:	NO
Suitable for emergency lighting:	NO	Dimming Touch and Dim:	NO
Material cover:	Plastic, opal	Dimming Zigbee:	NO
Pendant length:	1500/1500 mm	Dimming with push-button:	NO
Nominal voltage:	220/240 V	No dim function:	NO
Emergency power supply integrated:	NO	Light distributor:	None
Degree of protection (IP):	IP20	Luminaire efficacy:	0 lm/W
With light source:	NO	Dimming DSI:	NO
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Compatible with Apple HomeKit:	NO
Suitable for number of light sources:	1	Compatible with Google Assistant:	NO
With control gear:	NO	Compatible with Amazon Alexa:	NO
With suspension:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for workplace according to EN 12464-1:	NO	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Nominal current:	NA/NA mA	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Colour temperature:	NA/NA K	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Max. system power:	0 W	Dimming DALI-2:	NO
Rated luminous flux according to IEC 62722-2-1:	0 lm	Exchangeable control gear:	NO

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box
<p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product!</p>	
STATISTICS	85444290

