

## Elba pendel kit ball brass + rosette white + 1,5m white cable



|                 |   |
|-----------------|---|
| ARTICLE_NUMBER: | 800022.00A  |
| CHANGED_LAST:   | 23-05-2025  |
| BRAND:          | Daylight Italia   |
| ETIM_GROUP:     | EG000027 - Luminaires   |
| ETIM_CLASS:     | EC001743 - Pendant luminaire  |
| SYNONYM:        | Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire |



## FEATURES

|  |                  |  |        |
|--|------------------|--|--------|
| Width:   | 80 mm            | Constant light output (CLO):   | NO     |
| Reflector:   | None             | IFTTT support available:   | NO     |
| Lamp holder:   | E27              | Rated lifetime L70/B50 at 25 °C:   | 0 h    |
| Conductor cross section:   | 0 mm²            | Dimming 0-10 V:  | NO     |
| Connection type:   | Push-in clamp    | Dimming 1-10 V:  | NO     |
| Housing colour:  | Gold             | Dimming DALI:  | NO     |
| Suitable for lamp power:   | NA/NA W          | Dimming DMX:   | NO     |
| Type of grid:  | High-gloss       | Dimming potentiometer (integrated):  | NO     |
| Type of control gear:  | Not required     | Dimming LineSwitch:  | NO     |
| Diameter:  | 80 mm            | Dimming manufacturer's proprietary system:                                 | NO     |
| Length:  | 1500 mm          | Dimming mains voltage modulation:  | NO     |
| Height/depth:  | 80 mm            | Dimming phase cut-off (trailing edge):                                     | NO     |
| Housing material:  | Plastic          | Dimming phase cut-on (leading edge):                                       | NO     |
| Lamp type:   | LED exchangeable | Dimming programmable:  | NO     |
| Direct-/indirect proportion separately controllable:                             | NO               | Dimming RF:  | NO     |
| Suitable for light line configuration:   | NO               | Dimming Sine Wave Reduction:   | NO     |
| Suitable for emergency lighting:   | NO               | Dimming Touch and Dim:   | NO     |
| Material cover:  | Plastic, opal    | Dimming Zigbee:  | NO     |
| Pendant length:  | 1500/1500 mm     | Dimming with push-button:  | NO     |
| Nominal voltage:   | 220/240 V        | No dim function:   | NO     |
| Emergency power supply integrated:   | NO               | Light distributor:   | None   |
| Degree of protection (IP):   | IP20             | Luminaire efficacy:  | 0 lm/W |
| With light source:   | NO               | Dimming DSI:   | NO     |
| Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | NO               | Compatible with Apple HomeKit:   | NO     |
| Suitable for number of light sources:  | 1                | Compatible with Google Assistant:  | NO     |
| With control gear:   | NO               | Compatible with Amazon Alexa:  | NO     |
| With suspension:   | NO               | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 %    |
| Suitable for workplace according to EN 12464-1:                                  | NO               | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq): | 0 %    |
| Nominal current:   | NA/NA mA         | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):      | 0 %    |
| Colour temperature:  | NA/NA K          | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):      | 0 %    |
| Max. system power:   | 0 W              | Dimming DALI-2:  | NO     |
| Rated luminous flux according to IEC 62722-2-1:                                  | 0 lm             | Exchangeable control gear:   | NO     |

## PACKING\_INFORMATION

|  |          |
|--|----------|
| WEIGHT   | 0 gr     |
| PACKING_CODE   | BX       |
| PACKING_FORM   | Box      |
| <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product!</p> |          |
| STATISTICS   | 85444290 |

