

Satellite wall lamp complete E27 base silver



ARTICLE_NUMBER: 810211.00A

CHANGED_LAST: 23-05-2025

BRAND: Daylight Italia

ETIM_GROUP: EG000027 - Luminaires

ETIM_CLASS: EC002892 - Ceiling-/wall luminaire

SYNONYM: Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire



FEATURES

Width:	130 mm	With air slots:	NO
Outer diameter:	125 mm	Constant light output (CLO):	NO
Lamp holder:	E27	IFTTT support available:	NO
Conductor cross section:	0 mm²	Rated lifetime L70/B50 at 25 °C:	15000 h
Housing colour:	Silver	Rated ambient temperature according to IEC 62722-2-1:	NA/NA °C
Voltage type:	AC	Dimming 0-10 V:	NO
With movement sensor:	NO	Dimming 1-10 V:	NO
Suitable for lamp power:	NA/NA W	Dimming DALI:	NO
Type of grid:	Matt	Dimming DMX:	NO
Type of control gear:	Not required	Dimming potentiometer (integrated):	NO
Colour rendering index CRI:	90-100	Dimming LineSwitch:	NO
Built-in width:	0 mm	Dimming manufacturer's proprietary system:	NO
Built-in diameter:	0 mm	Dimming mains voltage modulation:	NO
With light sensor:	NO	Dimming phase cut-off (trailing edge):	NO
Suitable for suspended mounting:	NO	Dimming phase cut-on (leading edge):	NO
Luminous intensity:	0 cd	Dimming programmable:	NO
Length:	245 mm	Dimming RF:	NO
Height/depth:	130 mm	Dimming Sine Wave Reduction:	NO
Housing material:	Plastic	Dimming Touch and Dim:	NO
Lamp type:	LED exchangeable	Dimming Zigbee:	NO
Built-in length:	0 mm	Dimming with push-button:	NO
Suitable for light line configuration:	NO	No dim function:	NO
Suitable for emergency lighting:	NO	Light distributor:	Other
Light outlet:	Direct	Luminaire efficacy:	116 lm/W
Light distribution:	Symmetric	Dimming DSI:	NO
Material cover:	Plastic matt/satinized	Operation by Bluetooth:	NO
Nominal voltage:	220/240 V	Compatible with Apple HomeKit:	NO
Emergency power supply integrated:	NO	Compatible with Google Assistant:	NO
Degree of protection (IP):	IP20	Compatible with Amazon Alexa:	NO
With light source:	NO	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Covering of the luminaire with thermally insulating material possible:	NO	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for number of light sources:	1	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for built-in mounting:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With control gear:	NO	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for workplace according to EN 12464-1:	NO	Dimming DALI-2:	NO
Suitable for surface mounting:	NO	Colour of light adjustable:	No
Beam angle:	Variable beam angle	Luminous flux adjustable:	Continuously variable
Nominal current:	NA/NA mA	Beam angle adjustable:	Continuously variable
Colour temperature:	2700/2700 K	Exchangeable control gear:	NO
Max. system power:	0 W	Suitable for ceiling mounting:	NO
Rated luminous flux according to IEC 62722-2-1:	470 lm	Built-in height/depth:	0 mm
Colour of light:	White	Surface protection housing:	Other

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box
A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product.	
STATISTICS	94051041

