

## Led Downlight Jolly S quatro 85x85 CO75mm White-Gold GU10 LH



ARTICLE_NUMBER:	570140.00A
CHANGED_LAST:	26-05-2025
BRAND:	Daylight Italia
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001744 - Downlight/spot/floodlight
SYNONYM:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight



## FEATURES

Width:	85 mm	Suitable for light-track mounting:	NO
Outer diameter:	85 mm	Suitable for clamp-mounting:	NO
Reflector:	Matt	Constant light output (CLO):	NO
Lamp holder:	GU10	IFTTT support available:	NO
Conductor cross section:	0 mm²	Luminous flux:	NA/NA lm
Housing colour:	White	Rated lifetime L70/B50 at 25 °C:	0 h
Surface protection:	Lacquered	Rated ambient temperature according to IEC 62722-2-1:	NA/NA °C
With movement sensor:	NO	Dimming 0-10 V:	NO
Suitable for lamp power:	NA/NA W	Dimming 1-10 V:	NO
Suitable for wall mounting:	NO	Dimming DALI:	NO
Built-in width:	75 mm	Dimming DMX:	NO
With light sensor:	NO	Dimming potentiometer (integrated):	NO
Suitable for suspended mounting:	NO	Dimming LineSwitch:	NO
Luminous intensity:	0 cd	Dimming manufacturer's proprietary system:	NO
Length:	85 mm	Dimming mains voltage modulation:	NO
Height/depth:	32 mm	Dimming phase cut-off (trailing edge):	NO
Housing material:	Aluminium	Dimming phase cut-on (leading edge):	NO
Lamp type:	LED exchangeable	Dimming programmable:	NO
Built-in length:	75 mm	Dimming RF:	NO
Light outlet:	Direct	Dimming Sine Wave Reduction:	NO
Light distribution:	Symmetric	Dimming Touch and Dim:	NO
Material cover:	None	Dimming Zigbee:	NO
Nominal voltage:	220/240 V	Dimming with push-button:	NO
Emergency power supply integrated:	NO	No dim function:	NO
Degree of protection (IP):	IP20	Light distributor:	None
With light source:	NO	Luminaire efficacy:	0 lm/W
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Suitable for low voltage cable system:	NO
Covering of the luminaire with thermally insulating material possible:	NO	Dimming DSI:	NO
Suitable for number of light sources:	1	Compatible with Apple HomeKit:	NO
Suitable for built-in mounting:	NO	Compatible with Google Assistant:	NO
With control gear:	NO	Compatible with Amazon Alexa:	NO
Suitable for workplace according to EN 12464-1:	NO	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for surface mounting:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Connectable conductor cross section:	NA/NA mm²	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
Surface brushed:	NO	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Colour temperature:	NA/NA K	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Max. system power:	50 W	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
Rated luminous flux according to IEC 62722-2-1:	0 lm	Dimming DALI-2:	NO
Colour of light:	White	Exchangeable control gear:	NO
Adjustability:	Not adjustable	Built-in diameter:	75/75 mm
Suitable for traverse mounting:	NO	Suitable for ceiling mounting:	NO
Suitable for pedestal/floor mounting:	NO	Built-in height/depth:	30 mm

## PACKING\_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box
A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product.	
STATISTICS	85389099



Included

