

## LED Tri-Proof Light 200-240V 45W 4000K 6300Lm ND 1.5m



The **Toplux TX 10301013** is a robust and energy-efficient LED luminaire from the **LOCK&LOCK series**, designed for demanding industrial and commercial applications. With a power rating of **45W** and a light color of **4000K (neutral white)**, this luminaire delivers a powerful light output of **6300 lumens**, making it ideal for workshops, warehouses, parking garages, and other functional spaces.

ARTICLE\_NUMBER: TX 10301013

CHANGED\_LAST: 25-06-2025

BRAND: Toplux

ETIM\_GROUP: EG000027 - Luminaires

ETIM\_CLASS: EC000109 - Batten luminaire

SYNONYM: Batten luminaire, Device carrier,  
Fluorescent batten, Wall luminaire



## FEATURES

Protection class according to IEC 61140:	I	Rated lifetime L70/B50 at 25 °C:	50000 h
Width:	74 mm	Rated lifetime L70/B50 at 25 °C:	50000 h
Lamp holder:	None	Dimming 0-10 V:	NO
Conductor cross section:	-mm <sup>2</sup>	Dimming 1-10 V:	NO
Connection type:	Other	Dimming DALI:	NO
Housing colour:	Grey	Dimming DMX:	NO
Dimmable:	NO	Dimming potentiometer (integrated):	NO
Voltage type:	AC	Dimming LineSwitch:	NO
With movement sensor:	NO	Dimming manufacturer's proprietary system:	NO
Suitable for lamp power:	45 W	Dimming mains voltage modulation:	NO
Type of control gear:	Not required	Dimming phase cut-off (trailing edge):	NO
Colour rendering index CRI:	80-89	Dimming phase cut-on (leading edge):	NO
Diameter:	-mm	Dimming programmable:	NO
With switch:	NO	Dimming RF:	NO
With light sensor:	NO	Dimming Sine Wave Reduction:	NO
With light sensor:	NO	Dimming Touch and Dim:	NO
Length:	1500 mm	Dimming Zigbee:	NO
Height/depth:	64 mm	Dimming with push-button:	NO
Material:	Plastic	No dim function:	NO
Lamp type:	LED not exchangeable	Light distributor:	Other
With presence detector:	NO	Luminaire efficacy:	6300 lm/W
Electrical connection with connector system:	NO	Dimming DSI:	NO
Suitable for emergency lighting:	NO	Operation by Bluetooth:	NO
Impact strength:	IK08	Compatible with Apple HomeKit:	NO
Nominal voltage:	220 ~ 240	Compatible with Google Assistant:	NO
Emergency power supply integrated:	NO	Compatible with Amazon Alexa:	NO
Degree of protection (IP):	IP65	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
With light source:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Dimming DALI-2:	NO
Covering of the luminaire with thermally insulating material possible:	NO	Colour of light adjustable:	No
Covering of the luminaire with thermally insulating material possible:	NO	Luminous flux adjustable:	No
With control gear:	NO	Beam angle adjustable:	No
Connectable conductor cross section:	1.5 mm <sup>2</sup>	Exchangeable control gear:	NO
Luminous flux in emergency mode:	-lm	Compatible with Casambi:	NO
Nominal current:	196 mA	Energy efficiency class of the light source according to EU regulation 2019/2015:	B
Colour temperature:	4000 K	With lamp protection basket:	NO
Max. system power:	-W	With lamp protection basket:	NO
Rated luminous flux according to IEC 62722-2-1:	6300 lm	With lamp protection basket:	NO
Colour of light:	White	With lamp protection basket:	NO
Constant light output (CLO):	NO	With lamp protection basket:	NO
IFTTT support available:	NO	With lamp protection basket:	NO
Type of wiring:	Suitable for loop-through wiring	With lamp protection basket:	NO
Rated lifetime L70/B50 at 25 °C:	50000 h	Power factor:	0.95

## PACKING\_INFORMATION

WEIGHT	0 kg
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p>
STATISTICS	94051140

