

LED Flood light 100-277V 150W 4000K 120X150°



The **Toplux TX 10201260** from the **Slim G3 series** is a high-performance LED floodlight designed for maximum efficiency in demanding environments. With a power rating of **150W** and a light color of **4000K (neutral white)**, this floodlight delivers an impressive luminous output of approximately **20,000–22,500 lumens**, making it ideal for illuminating large outdoor areas, construction sites, parking lots, and industrial zones.

Thanks to the **Philips LED module** and the reliable **Sosen driver**, this fixture offers excellent energy efficiency (indicative energy label **B**) and a long lifespan of **50,000 hours**. The robust aluminum housing with **IP66 protection** and **IK08 impact resistance** ensures durability under all weather conditions

ARTICLE_NUMBER:	TX 10201260
CHANGED_LAST:	25-06-2025
BRAND:	Toplux
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001744 - Downlight/spot/floodlight
SYNONYM:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight



FEATURES

Protection class according to IEC 61140:	I	Built-in width:	- mm
Width:	-mm	Colour consistency (McAdam ellipse):	SDCM6
Outer diameter:	-mm	Colour consistency (McAdam ellipse):	SDCM6
Reflector:	None	Colour consistency (McAdam ellipse):	SDCM6
Lamp holder:	None	Colour consistency (McAdam ellipse):	SDCM6
Conductor cross section:	-mm²	Rated ambient temperature according to IEC 62722-2-1:	- °C
Connection type:	Free conductor end	Rated ambient temperature according to IEC 62722-2-1:	- °C
Housing colour:	Black	Dimming 0-10 V:	NO
Dimmable:	NO	Dimming 1-10 V:	NO
Surface protection:	Powder coating	Dimming DALI:	NO
Voltage type:	AC	Dimming DMX:	NO
With movement sensor:	NO	Dimming potentiometer (integrated):	NO
Suitable for lamp power:	150 W	Dimming LineSwitch:	NO
Type of control gear:	Electronic ballast	Dimming manufacturer's proprietary system:	NO
Colour rendering index CRI:	70-79	Dimming mains voltage modulation:	NO
Suitable for wall mounting:	NO	Dimming phase cut-off (trailing edge):	NO
Built-in width:	-mm	Dimming phase cut-on (leading edge):	NO
With light sensor:	NO	Dimming programmable:	NO
Suitable for suspended mounting:	NO	Dimming RF:	NO
Luminous intensity:	-cd	Dimming Sine Wave Reduction:	NO
Luminous intensity:	-cd	Dimming Touch and Dim:	NO
Length:	-mm	Dimming Zigbee:	NO
Height/depth:	-mm	Dimming with push-button:	NO
Housing material:	Aluminium	No dim function:	NO
Lamp type:	LED not exchangeable	Light distributor:	Diffuser lens/optic/panel
Reflector colour:	Other	Luminaire efficacy:	-lm/W
With presence detector:	NO	Suitable for low voltage cable system:	NO
With presence detector:	NO	Dimming DSI:	NO
Built-in length:	-mm	Dimming DSI:	NO
Light outlet:	Direct	Operation by Bluetooth:	NO
Light distribution:	Asymmetric	Compatible with Apple HomeKit:	NO
Material cover:	Glass transparent	Compatible with Google Assistant:	NO
Impact strength:	IK08	Compatible with Amazon Alexa:	NO
Nominal voltage:	100 ~ 277	Compatible with Amazon Alexa:	NO
Emergency power supply integrated:	NO	Compatible with Amazon Alexa:	NO
Degree of protection (IP):	IP66	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	-%
With light source:	NO	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	-%
Covering of the luminaire with thermally insulating material possible:	NO	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	-%
Covering of the luminaire with thermally insulating material possible:	NO	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	-%
Suitable for built-in mounting:	NO	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	-%
With control gear:	NO	Dimming DALI-2:	NO
Suitable for workplace according to EN 12464-1:	NO	Dimming DALI-2:	NO
Suitable for surface mounting:	NO	Dimming DALI-2:	NO
Beam angle:	> 80° - Extreme wide beam	Colour of light adjustable:	No

Connectable conductor cross section:	- mm²	Luminous flux adjustable:	No
Surface brushed:	NO	Beam angle adjustable:	No
Luminous flux in emergency mode:	-lm	Exchangeable control gear:	NO
Nominal current:	652 mA	Built-in diameter:	- mm
Colour temperature:	4000 K	Compatible with Casambi:	NO
Max. system power:	150 W	Energy efficiency class of the light source according to EU regulation 2019/2015:	B
Rated luminous flux according to IEC 62722-2-1:	25500 lm	Luminous intensity:	- cd
Colour of light:	White	Luminous intensity:	- cd
Adjustability:	Swivelling	Luminous intensity:	- cd
Suitable for traverse mounting:	NO	Luminous intensity:	- cd
Suitable for pedestal/floor mounting:	NO	Luminous intensity:	- cd
Suitable for light-track mounting:	NO	Luminous intensity:	- cd
Suitable for clamp-mounting:	NO	Luminous intensity:	- cd
Constant light output (CLO):	NO	Luminous intensity:	- cd
Built-in height:	- mm	Luminous intensity:	- cd
IFTTT support available:	NO	Luminous intensity:	- cd
Luminous flux:	25500 lm	Suitable for ceiling mounting:	NO
Luminous flux:	25500 lm	Suitable for ceiling mounting:	NO
Rated lifetime L70/B50 at 25 °C:	50000 h	Built-in height/depth:	-mm
Rated lifetime L70/B50 at 25 °C:	50000 h	Power factor:	0.95

PACKING_INFORMATION

WEIGHT	0 kg
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the product</p>
STATISTICS	94054210

