![vezalux - light for everyone since 1991]

Wernhoutseweg 38A
4884 AW Wernhout
The Netherlands

+31 (0)76 - 59 712 20
info@vezalux.nl
www.vezalux.com

Osram Quicktronic M 1x26...42 2x26

The **QTP-T/E 1X26…42, 2X26** ballast is designed to regulate the current to fluorescent lamps or other gas discharge lamps. This device ensures that the lamps start up correctly and continue to operate without flickering. It is suitable for use in various lighting systems, including office lighting, commercial lighting, industrial lighting, and public lighting.

ARTICLE_NUMBER:	OSR 537089
CHANGED_LAST:	26-06-2025
BRAND:	OSRAM
ETIM_GROUP:	EG000030 - Accessories for lighting
ETIM_CLASS:	EC001497 - Ballast (electrical)
SYNONYM:	Ballast, Conventional ballast, Conversion kit, Low-loss ballast, Ballast (electrical), Choke ballast

4 0 0 8 3 2 1 5 3 7 0 8 9

Wernhoutseweg 38A
4884 AW Wernhout
The Netherlands

+31 (0)76 - 59 712 20
info@vezalux.nl
www.vezalux.com

FEATURES

Protection class according to IEC 61140:	I	Suitable for lamp power (1 lamp):	26 ~ 42
Width:	67 mm	Suitable for lamp power (2 lamps):	26 W
Model:	Electronic	Suitable for lamp power (3 lamps):	- W
Height:	31 mm	Suitable for lamp power (4 lamps):	- W
Dimmable:	NO	Multiwatt model:	NO
Housing:	Plastic housing	Suitable for number of lamps:	2
Suitable for lamp power:	26 ~ 42	IFTTT support available:	NO
With strain relief:	NO	Dimming 0-10 V:	NO
Length:	103 mm	Dimming 1-10 V:	NO
For lamp type TC-D:	NO	Dimming DALI:	NO
For lamp type TC-DD:	NO	Dimming DMX:	NO
For lamp type TC-L:	NO	Dimming potentiometer (integrated):	NO
For lamp type TC-DEL:	NO	Dimming LineSwitch:	NO
For lamp type TC-TEL:	NO	Dimming manufacturer's proprietary system:	NO
For lamp type T7:	NO	Dimming mains voltage modulation:	NO
For lamp type T16:	NO	Dimming phase cut-off (trailing edge):	NO
For lamp type T26:	NO	Dimming phase cut-on (leading edge):	NO
For lamp type T-R:	NO	Dimming programmable:	NO
For lamp type TC-T:	NO	Dimming RF:	NO
For lamp type TC-S:	NO	Dimming Sine Wave Reduction:	NO
For lamp type HI:	NO	Dimming Touch and Dim:	NO
Nominal voltage:	220 ~ 240	Dimming Zigbee:	NO
Degree of protection (IP):	IP20	Dimming with push-button:	NO
For lamp type HM:	NO	No dim function:	NO
For lamp type HS:	NO	Dimming DSI:	NO
For lamp type LS:	NO	Operation by Bluetooth:	NO
For lamp type T16-R:	NO	Compatible with Apple HomeKit:	NO
For lamp type T38:	NO	Compatible with Google Assistant:	NO
For lamp type TC-F:	NO	Compatible with Amazon Alexa:	NO
For lamp type TC-QEL:	NO	Dimming DALI-2:	NO
For lamp type TC-SEL:	NO	Compatible with Casambi:	NO
For lamp type T-U:	NO		

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the producthi
STATISTICS	85041080

Wernhoutseweg 38A
4884 AW Wernhout
The Netherlands

+31 (0)76 - 59 712 20
info@vezalux.nl
www.vezalux.com