

HALUX Downlight Slim 6W 400Lm CCT 2700/3000K white DIM




HALUX Downlight Slim 6W DIMMABLE CCT 2700K/3000K

The HALUX Downlight Slim is a high-quality, dimmable LED downlight ideal for both residential and commercial applications. With a power rating of 6W and a light output of 400 lumens, this downlight provides warm and inviting illumination with a color temperature range of 2700K to 3000K. It features a 36° beam angle and a high color rendering index (Ra>95), ensuring true-to-life color representation. The flicker-free technology and white RAL9003 finish make this downlight a seamless fit for any interior. It has a cut size of 68mm and an IP44 protection rating, making it suitable for use in damp environments such as bathrooms. The internal driver ensures easy installation and reliable operation.

Key Features:

- Power: 6W
- Light Output: 400 lumens
- Color Temperature: 2700K/3000K
- Beam Angle: 36°
- Color Rendering Index: Ra>95
- Flicker-Free
- White Finish (RAL9003)
- Cut Size: 68mm
- Protection Rating: IP44
- Internal Driver

ARTICLE_NUMBER:	TH 03117
CHANGED_LAST:	27-06-2025
BRAND:	Thorgeon
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001702 - Downlight rigid/swivelling
SYNONYM:	Downlight, Downlight rigid, Downlight rigid/swivelling, Downlight swivelling, Spot



FEATURES

Protection class according to IEC 61140:	II	Material cover:	Double asymmetric
Width:	-mm	Impact strength:	IK04
Outer diameter:	85 mm	Nominal voltage:	220 ~ 240
Reflector:	High-gloss	Degree of protection (IP):	IP44
Lamp holder:	None	With light source:	YES
Housing colour:	White	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO
Voltage type:	AC	Covering of the luminaire with thermally insulating material possible:	NO
With movement sensor:	NO	Suitable for number of light sources:	1
Built-in depth:	-mm	Surface finishing:	Matt
Suitable for lamp power:	6 W	Suitable for wall mounting:	NO
Type of grid:	None	Suitable for built-in mounting:	YES
Type of control gear:	Not required	With control gear:	NO
Colour rendering index CRI:	90-100	Suitable for workplace according to EN 12464-1:	NO
Built-in width:	68 mm	Suitable for surface mounting:	NO
Built-in diameter:	68 mm	Lamp power at multiwatt:	Not applicable
With light sensor:	NO	Beam angle:	21-40° - Medium beam
Suitable for suspended mounting:	NO	Type of dimming:	Other
Length:	31 mm	Emergency unit integrated:	NO
Height/depth:	-mm	Nominal current:	- mA
Housing material:	Other	Colour temperature:	2700 ~ 3000
Ambient temperature:	- °C	Max. system power:	6 W
Lamp type:	LED not exchangeable	Filament test according to IEC 60695-2-10:	6 W
Built-in length:	68 mm	Rated luminous flux according to IEC 62722-2-1:	400 lm
Light outlet:	Direct	Colour of light:	White
Light distribution:	Double asymmetric	Adjustability:	Swivelling
Material cover:	Double asymmetric	Suitable for ceiling mounting:	YES

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product
STATISTICS	94051190

