

HALUX Downlight Slim 6W 400Lm CCT 2700/3000K black DIM




HALUX Downlight Slim 6W DIMMABLE CCT 2700K/3000K

The HALUX Downlight Slim is a high-quality, dimmable LED downlight ideal for both residential and commercial applications. With a power rating of 6W and a light output of 400 lumens, this downlight provides warm and inviting illumination with a color temperature range of 2700K to 3000K. It features a 36° beam angle and a high color rendering index (Ra>95), ensuring true-to-life color representation. The flicker-free technology and black RAL9005 finish make this downlight a seamless fit for any interior. It has a cut size of 68mm and an IP44 protection rating, making it suitable for use in damp environments such as bathrooms. The internal driver ensures easy installation and reliable operation.

Key Features:

- Power: 6W
- Light Output: 400 lumens
- Color Temperature: 2700K/3000K
- Beam Angle: 36°
- Color Rendering Index: Ra>95
- Flicker-Free
- Black Finish (RAL9005)
- Cut Size: 68mm
- Protection Rating: IP44
- Internal Driver

| | |
|-----------------|--|
| ARTICLE_NUMBER: | TH 03119 |
| CHANGED_LAST: | 27-06-2025 |
| BRAND: | Thorgeon |
| ETIM_GROUP: | EG000027 - Luminaires |
| ETIM_CLASS: | EC001702 - Downlight rigid/swivelling |
| SYNONYM: | Downlight, Downlight rigid, Downlight rigid/swivelling, Downlight swivelling, Spot |



FEATURES

| | | | |
|--|----------------------|--|----------------------|
| Protection class according to IEC 61140: | II | Material cover: | Double asymmetric |
| Width: | -mm | Impact strength: | IK04 |
| Outer diameter: | 85 mm | Nominal voltage: | 220 ~ 240 |
| Reflector: | High-gloss | Degree of protection (IP): | IP44 |
| Lamp holder: | None | With light source: | YES |
| Housing colour: | Black | Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | NO |
| Voltage type: | AC | Covering of the luminaire with thermally insulating material possible: | NO |
| With movement sensor: | NO | Suitable for number of light sources: | 1 |
| Built-in depth: | -mm | Surface finishing: | Matt |
| Suitable for lamp power: | 6 W | Suitable for wall mounting: | NO |
| Type of grid: | None | Suitable for built-in mounting: | YES |
| Type of control gear: | Not required | With control gear: | NO |
| Colour rendering index CRI: | 90-100 | Suitable for workplace according to EN 12464-1: | NO |
| Built-in width: | 68 mm | Suitable for surface mounting: | NO |
| Built-in diameter: | 68 mm | Lamp power at multiwatt: | Not applicable |
| With light sensor: | NO | Beam angle: | 21-40° - Medium beam |
| Suitable for suspended mounting: | NO | Type of dimming: | Other |
| Length: | 31 mm | Emergency unit integrated: | NO |
| Height/depth: | -mm | Nominal current: | - mA |
| Housing material: | Other | Colour temperature: | 2700 ~ 3000 |
| Ambient temperature: | - °C | Max. system power: | 6 W |
| Lamp type: | LED not exchangeable | Filament test according to IEC 60695-2-10: | 6 W |
| Built-in length: | 68 mm | Rated luminous flux according to IEC 62722-2-1: | 400 lm |
| Light outlet: | Direct | Colour of light: | White |
| Light distribution: | Double asymmetric | Adjustability: | Swivelling |
| Material cover: | Double asymmetric | Suitable for ceiling mounting: | YES |

PACKING_INFORMATION

| | |
|--------------|--|
| WEIGHT | 0 gr |
| PACKING_CODE | BX |
| PACKING_FORM | Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p> |
| STATISTICS | 94051190 |

