

## HALUX Downlight Slim 6W 400Lm CCT 2700/3000K Brushed nickel DIM




### HALUX Downlight Slim 6W DIMMABLE CCT 2700K/3000K

The HALUX Downlight Slim is a high-quality, dimmable LED downlight ideal for both residential and commercial applications. With a power rating of 6W and a light output of 400 lumens, this downlight provides warm and inviting illumination with a color temperature range of 2700K to 3000K. It features a 36° beam angle and a high color rendering index (Ra>95), ensuring true-to-life color representation. The flicker-free technology and brushed nickel finish make this downlight a seamless fit for any interior. It has a cut size of 68mm and an IP44 protection rating, making it suitable for use in damp environments such as bathrooms. The internal driver ensures easy installation and reliable operation.

#### Key Features:

- Power: 6W
- Light Output: 400 lumens
- Color Temperature: 2700K/3000K
- Beam Angle: 36°
- Color Rendering Index: Ra>95
- Flicker-Free
- Brushed nickel
- Cut Size: 68mm
- Protection Rating: IP44
- Internal Driver

ARTICLE_NUMBER:	TH 03121
CHANGED_LAST:	27-06-2025
BRAND:	Thorgeon
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001702 - Downlight rigid/swivelling
SYNONYM:	Downlight, Downlight rigid, Downlight rigid/swivelling, Downlight swivelling, Spot



## FEATURES

Protection class according to IEC 61140:	II	Impact strength:	IK04
Width:	-mm	Nominal voltage:	220 ~ 240
Outer diameter:	85 mm	Degree of protection (IP):	IP44
Reflector:	High-gloss	With light source:	YES
Lamp holder:	None	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO
Housing colour:	Nickel	Covering of the luminaire with thermally insulating material possible:	NO
Voltage type:	AC	Suitable for number of light sources:	1
With movement sensor:	NO	Surface finishing:	Glossy
Built-in depth:	-mm	Suitable for wall mounting:	NO
Suitable for lamp power:	6 W	Suitable for built-in mounting:	YES
Type of grid:	None	With control gear:	NO
Type of control gear:	Not required	Suitable for workplace according to EN 12464-1:	NO
Colour rendering index CRI:	90-100	Suitable for surface mounting:	NO
Built-in width:	68 mm	Lamp power at multiwatt:	Not applicable
Built-in diameter:	68 mm	Beam angle:	21-40° - Medium beam
With light sensor:	NO	Type of dimming:	Other
Suitable for suspended mounting:	NO	Emergency unit integrated:	NO
Length:	31 mm	Nominal current:	- mA
Height/depth:	-mm	Colour temperature:	2700 ~ 3000
Housing material:	Other	Max. system power:	6 W
Ambient temperature:	- °C	Filament test according to IEC 60695-2-10:	6 W
Lamp type:	LED not exchangeable	Rated luminous flux according to IEC 62722-2-1:	400 lm
Built-in length:	68 mm	Colour of light:	White
Light outlet:	Direct	Adjustability:	Swivelling
Light distribution:	Double asymmetric	Suitable for ceiling mounting:	YES

## PACKING\_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p>
STATISTICS	94051190

