

# HALUX Downlight Slim 6W 400Lm 2100-2700K brushed nickel DTW




## HALUX Downlight Slim 6W Dim-to-Warm 2100-2700K - Brushed Nickel

The HALUX Downlight Slim 6W is a high-quality LED downlight ideal for both residential and commercial applications. This downlight features a dim-to-warm function, allowing the color temperature to range from 2100K to 2700K, creating a warm and inviting atmosphere. With a light output of 400 lumens and a 36° beam angle, this downlight provides excellent illumination. The high color rendering index (Ra>95) ensures true-to-life colors. The downlight is flicker-free and has a brushed nickel finish, making it a seamless fit for any interior. It has a cut size of 68mm and an IP44 protection rating, making it suitable for use in damp environments such as bathrooms. The internal driver ensures easy installation and reliable operation.

### Key Features:

- Power: 6W
- Light Output: 400 lumens
- Color Temperature: 2100K-2700K (Dim-to-Warm)
- Beam Angle: 36°
- Color Rendering Index: Ra>95
- Flicker-Free
- Brushed Nickel Finish
- Cut Size: 68mm
- Protection Rating: IP44
- Internal Driver

ARTICLE_NUMBER:	TH 03122
CHANGED_LAST:	27-06-2025
BRAND:	Thorgeon
ETIM_GROUP:	EG000027 - Luminaires
ETIM_CLASS:	EC001702 - Downlight rigid/swivelling
SYNONYM:	Downlight, Downlight rigid, Downlight rigid/swivelling, Downlight swivelling, Spot



## FEATURES

Protection class according to IEC 61140:	II	Material cover:	Double asymmetric
Width:	-mm	Impact strength:	IK04
Outer diameter:	85 mm	Nominal voltage:	220 ~ 240
Reflector:	High-gloss	Degree of protection (IP):	IP44
Lamp holder:	None	With light source:	YES
Housing colour:	White	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	NO
Voltage type:	AC	Covering of the luminaire with thermally insulating material possible:	NO
With movement sensor:	NO	Suitable for number of light sources:	1
Built-in depth:	-mm	Surface finishing:	Matt
Suitable for lamp power:	6 W	Suitable for wall mounting:	NO
Type of grid:	None	Suitable for built-in mounting:	YES
Type of control gear:	Not required	With control gear:	NO
Colour rendering index CRI:	90-100	Suitable for workplace according to EN 12464-1:	NO
Built-in width:	68 mm	Suitable for surface mounting:	NO
Built-in diameter:	68 mm	Lamp power at multiwatt:	Not applicable
With light sensor:	NO	Beam angle:	21-40° - Medium beam
Suitable for suspended mounting:	NO	Type of dimming:	Other
Length:	31 mm	Emergency unit integrated:	NO
Height/depth:	-mm	Nominal current:	- mA
Housing material:	Other	Colour temperature:	2100 ~ 2700
Ambient temperature:	- °C	Max. system power:	6 W
Lamp type:	LED not exchangeable	Filament test according to IEC 60695-2-10:	6 W
Built-in length:	68 mm	Rated luminous flux according to IEC 62722-2-1:	400 lm
Light outlet:	Direct	Colour of light:	White
Light distribution:	Double asymmetric	Adjustability:	Swivelling
Material cover:	Double asymmetric	Suitable for ceiling mounting:	YES

## PACKING\_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box <p>A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the product</p>
STATISTICS	94051190

