

Microwave switch sensor 1- 8m max 2000W IP20 white Thorgeon



Microwave switch sensor 1- 8m max 2000W IP20 white Thorgeon	
ARTICLE_NUMBER:	TH 02001
CHANGED_LAST:	25-10-2024
BRAND:	Thorgeon
ETIM_GROUP:	EG000013 - Domestic switching devices
ETIM_CLASS:	EC000133 - Movement sensor/presence detector complete
SYNONYM:	Auxiliary post, Movement sensor, Movement sensor / presence detector complete, Movement sensor complete, Movement sensor/presence detector complete, Multi-sensor, Presence detector



FEATURES

Mounting method:	Surface mounted	RAL-number (similar):	9010
Colour:	White	With signal unit:	NO
Width:	-mm	Control current:	-mA
Model:	Movement sensor	Teach-function for response value luminosity:	NO
Halogen free:	YES	Networkable:	NO
Height:	-mm	Forced switch off:	NO
Depth:	-mm	Scan angle:	360 °
Connection type:	Screw terminal	Built-in length:	-mm
Surface protection:	Untreated	Impact strength:	-mm
Creep-under protection:	NO	With connection cable:	-mm
Voltage type:	AC	Nominal voltage:	220 ~ 240
Switching-on delay:	-s	Degree of protection (IP):	IP20
Switch-off delay:	-s	With alarm function:	NO
Built-in depth:	-mm	Transparent:	NO
Frequency:	50 ~ 60	Animal zone:	NO
With remote control:	NO	Surface finishing:	Matt
Diameter:	115 mm	Detection angle horizontal:	- °
Suitable for wall mounting:	115 mm	Min. switch-on time:	10 s
Built-in width:	-mm	Max. duty cycle:	12 min
Built-in diameter:	-mm	Response value luminosity adjustable:	YES
Staircase light controller:	NO	Optimum mounting height:	2 m
Bridging switch:	NO	Pivoting range sensor, horizontal:	- °
Suitable for wireless transmission:	NO	Pivoting range sensor, vertical:	- °
Material quality:	Thermoplastic	Number of switching zones:	- °
Max. reach frontally:	8 m	With DALI interface:	NO
Max. reach sideways:	8 m	IFTTT support available:	NO
Max. switching power:	2000 W	Forced switch on:	NO
Temperature:	-20 ~ 40	Min. starting current:	-A
Max. starting current:	-A	Min. depth of built-in installation box:	-mm
Material:	Plastic	Max. presence range:	4 m ²
Ambient temperature:	Plastic	Compatible with Apple HomeKit:	NO
Response value sensitivity adjustable:	YES	Compatible with Google Assistant:	NO
Connection cable length:	YES	Compatible with Amazon Alexa:	NO
Dim function with dimmer basic element:	NO	Max. switching power LED:	1000 W
Response value luminosity:	3 ~ 2000	Compatible with Casambi:	1000 W
Suitable for C-load:	NO	Background monitoring:	1000 W
Diameter reach on floor:	-m	With acoustic sensor:	1000 W
Remote operation:	NO	Ceiling built-in mounting without installation box:	1000 W
HVAC-control:	NO	Movement sensor/presence detector technology:	1000 W
Constant light control:	YES	Sensor type:	High frequency
Substation input:	NO	Suitable for ceiling mounting:	YES
RAL-number (similar):	9010	Anti-bacterial treatment:	NO

PACKING INFORMATION

WEIGHT 0.12 kg

WIDTH	120 mm
HEIGHT	35 mm
LENGHT	155 mm
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one -off use, depending on the producti
STATISTICS	85365003

