





universal LED dimmer insert			
ARTICLE_NUMBER:	MTN5134-0000		
CHANGED_LAST:	06-08-2025		
BRAND:	Schneider Electric		
ETIM_GROUP:	EG000013 - Domestic switching devices		
ETIM_CLASS:	EC000025 - Dimmer		
SYNONYM:	Adapter plug, Dimmer, Plug adapter		









FEATURES

Mounting method:	Flush-mounted	Impact strength:	NO
Assembly arrangement:	Basic element	Nominal voltage:	230.000 V
Method of operation:	Turn/push button	Control voltage:	NA V
Colour:	Turn/push button	Transparent:	NO
Halogen free:	YES	Surface finishing:	NO
Number of units:	YES	Suitable for degree of protection (IP):	IP20
Connection type:	Screwed terminal	Core cross section:	1.500 ~ 2.500
Surface protection:	Untreated	Device width:	74 mm
Power consumption:	-W	Device height:	74 mm
Frequency:	50.000 ~ 60.000	Device depth:	29 mm
Material quality:	Other	Number of modules (module system):	29 mm
Type of load:	Universal and LED Retrofit	IFTTT support available:	NO
Material:	Other	Dimming phase cut-off (trailing edge):	YES
Type of fastening:	Mounting with claw and screw	Dimming phase cut-on (leading edge):	YES
Light value memory:	NO	Min. depth of built-in installation box:	40 mm
Substation input:	YES	App control via Bluetooth:	NO
RAL-number (similar):	YES	Nominal power resistive load:	10.000 ~ 400.000
Serial dimmer:	NO	Nominal power inductive load:	4.000 ~ 400.000
Applicable with movement sensor:	NO	Nominal power capacitive load:	4.000 ~ 400.000
Applicable with transmission button:	NO	Compatible with Apple HomeKit:	NO
Applicable with infrared button:	NO	Compatible with Google Assistant:	NO
Applicable with presence indicator:	NO	Compatible with Amazon Alexa:	NO
Applicable with button:	NO	Max. switching power LED:	200 W
Applicable with time switch/timer:	NO	Min. brightness controllable:	NO

PACKING_INFORMATION

WEIGHT	0 gr
PACKING_CODE	BX
PACKING_FORM	Box A non-specific term that refers to a non-flexible, three-dimensional packaging with closed sides that can be completely enveloped and made of any material. Although some boxes are suitable for reuse or rescue, they can also be for one-off use, depending on the producthic/p>
STATISTICS	8536508000



0





