

Downlight cabinet 176-264V 4W 2700K 260Lm 36Deg Ra90 nickel



| | |
|---|---|
| Downlight cabinet 176-264V 4W 2700K 260Lm 36Deg Ra90 nickel | |
| Article number: | CL 7018N |
| Status product: | 94E - Article ahead (GS1 Code) |
| Replacement code: | CL 47019 |
| Changed last: | 02-10-2024 |
| Brand: | Civilight |
| Type: | Cabinet |
| ETIM Group: | EG000027 - Luminaires |
| ETIM Classes: | EC001744 - Downlight/spot/floodlight |
| Synonym: | Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight |



Feature

| | | | |
|--|----------|--|-----------|
| Suitable for surface mounting: | No | Dimming with push-button: | No |
| Suitable for built-in mounting: | No | No dim function: | No |
| Suitable for wall mounting: | No | Rated life time L70/B50 at 25 °C: | 0 h |
| Suitable for suspended mounting: | No | Rated life time L80/B10 at 25 °C: | 0 h |
| Suitable for ceiling mounting: | No | Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for traverse mounting: | No | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for pedestal/floor mounting: | No | Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for light-track mounting: | No | Failure rate at median useful life of 35,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for clamp-mounting: | No | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for low voltage cable system: | No | Failure rate at median useful life of 100,000 h at 25 °C ambient (tq): | 0 % |
| With movement sensor: | No | Constant light output (CLO): | No |
| With light sensor: | No | Rated ambient temperature according to IEC 62722-2-1: | 0 ~ 0 °C |
| With light source: | No | Suitable for lamp power: | 0 ~ 0 W |
| Surface brushed: | No | Max. system power: | 0 W |
| Nominal voltage: | 0 ~ 0 V | Colour temperature: | 0 ~ 0 K |
| LED nominal current at constant current: | 0 ~ 0 mA | Luminous flux: | 0 ~ 0 lm |
| With control gear: | No | Rated luminous flux according to IEC 62722-2-1: | 0 lm |
| Exchangeable control gear: | No | Luminous intensity: | 0 cd |
| Dimming depending on control gear: | No | Width: | 0 mm |
| Dimming 0-10 V: | No | Height/depth: | 0 mm |
| Dimming 1-10 V: | No | Length: | 0 mm |
| Dimming DALI-2: | No | Outer diameter: | 0 mm |
| Dimming DALI: | No | Built-in width: | 0 mm |
| Dimming DMX: | No | Built-in height/depth: | 0 mm |
| Dimming DSI: | No | Built-in length: | 0 mm |
| Dimming potentiometer (integrated): | No | Built-in diameter: | 0 ~ 0 mm |
| Dimming GPRS: | No | Conductor cross section: | 0 mm² |
| Dimming LineSwitch: | No | Connectable conductor cross section: | 0 ~ 0 mm² |
| Dimming manufacturer's proprietary system: | No | Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | No |
| Dimming mains voltage modulation: | No | Emergency power supply integrated: | No |
| Dimming phase cut-off: | No | Luminaire efficacy: | 0 lm/W |
| Dimming phase cut-on: | No | Suitable for workplace according to EN 12464-1: | No |
| Dimming programmable: | No | Covering of the luminaire with thermally insulating material possible: | No |
| Dimming RF: | No | IFTTT support available: | No |
| Dimming Sine Wave Reduction: | No | Compatible with Apple HomeKit: | No |
| Dimming Touch and Dim: | No | Compatible with Google Assistant: | No |
| Dimming Zigbee: | No | Compatible with Amazon Alexa: | No |

Packaging data

Weight 0.07 kg

Customs code 85395100

