

## Cvitec ARTEMI AC 220-240V 18W 3000-2100K 900Lm Ra97 D2W



Cvitec ARTEMI AC 220-240V 18W 3000-2100K 900Lm Ra97 D2W	
Article number:	CT 60039
Status product:	94E - Article ahead (GS1 Code)
Changed last:	14-11-2024
Brand:	Cvitec
Type:	Artemi
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC001744 - Downlight/spot/floodlight
Synonym:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight



## Feature

Suitable for surface mounting:	No	Beam angle:	Wide beam 41-80°
Suitable for built-in mounting:	Yes	Light outlet:	Direct/indirect
Suitable for wall mounting:	No	Rated life time L70/B50 at 25 °C:	0 h
Suitable for suspended mounting:	No	Rated life time L80/B10 at 25 °C:	0 h
Suitable for ceiling mounting:	No	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for traverse mounting:	No	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for pedestal/floor mounting:	No	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
Suitable for light-track mounting:	No	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for clamp-mounting:	No	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for low voltage cable system:	No	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
With movement sensor:	No	Constant light output (CLO):	No
With light sensor:	No	Degree of protection (IP):	IP20
With light source:	No	Rated ambient temperature according to IEC 62722-2-1:	0 ~ 0 °C
Housing colour:	White	Suitable for lamp power:	0 ~ 0 W
Surface brushed:	No	Max. system power:	0 W
Voltage type:	AC	Colour of light:	White
Nominal voltage:	220 ~ 240 V	Colour temperature:	3000 ~ 2100 K
LED nominal current at constant current:	0 ~ 0 mA	Colour rendering index CRI:	90-100
With control gear:	Yes	Luminous flux:	900 ~ 900 lm
Exchangeable control gear:	No	Rated luminous flux according to IEC 62722-2-1:	0 lm
Dimming depending on control gear:	No	Luminous intensity:	0 cd
Dimming 0-10 V:	No	Power factor:	0.95
Dimming 1-10 V:	No	Width:	185 mm
Dimming DALI-2:	No	Height/depth:	52 mm
Dimming DALI:	No	Length:	0 mm
Dimming DMX:	No	Outer diameter:	185 mm
Dimming DSI:	No	Built-in width:	175 mm
Dimming potentiometer (integrated):	No	Built-in height/depth:	0 mm
Dimming GPRS:	No	Built-in length:	0 mm
Dimming LineSwitch:	No	Built-in diameter:	0 ~ 0 mm
Dimming manufacturer's proprietary system:	No	Conductor cross section:	0 mm²
Dimming mains voltage modulation:	No	Connectable conductor cross section:	0 ~ 0 mm²
Dimming phase cut-off:	No	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
Dimming phase cut-on:	No	Emergency power supply integrated:	No
Dimming programmable:	No	Luminaire efficacy:	0 lm/W
Dimming RF:	No	Suitable for workplace according to EN 12464-1:	No
Dimming Sine Wave Reduction:	No	Covering of the luminaire with thermally insulating material possible:	No
Dimming Touch and Dim:	No	IFTTT support available:	No
Dimming Zigbee:	No	Compatible with Apple HomeKit:	No
Dimming with push-button:	No	Compatible with Google Assistant:	No
No dim function:	No	Compatible with Amazon Alexa:	No
Reflector:	Matt		

### Packaging data

Weight	0.38 kg
Customs code	85395100

