

HaLed module AC 200-240V 9W 3000K 550Lm 24Degr. Ra95 Dim



HaLed module AC 200-240V 9W 3000K 550Lm 24Degr. Ra95 Dim	
Article number:	CT 47598
Status product:	126 - CURRENT
Changed last:	02-10-2024
Brand:	Cvitec
Type:	Haled III
ETIM Group:	EG000028 - Lamps
ETIM Classes:	EC001959 - LED-lamp/Multi-LED
Synonym:	Bulblamp, Candlelamp, Globelamp, Lamp, LED, LED candle, LED capsule, LED lamp, LED luster



Feature

Nominal voltage:	200 ~ 240 V	Colour consistency (McAdam ellipse):	SDCM5
Nominal current:	46 ~ 46 mA	Dimmable:	Yes
Power factor:	0.95	Diameter:	50 mm
Lamp power:	9 ~ 9 W	Length:	50 mm
Voltage type:	AC	Degree of protection (IP):	IP20
Luminous flux:	550 ~ 550 lm	Energy Efficiency Index (EEI):	0.19
Rated luminous flux according to IEC 62612:	550 lm	Lamp designation:	PAR16
Lamp efficacy:	61 lm/W	Energy efficiency class:	G
Luminous intensity:	1750 cd	Min. number of switching cycles:	100000
Colour rendering index CRI:	90-100	Weighted energy consumption in 1000 hours:	6 kWh
Lamp shape:	Reflector	Average nominal lifespan:	40000 h
Filament lamp:	No	Remote operation possible:	No
Type of glass/cover:	Clear	With remote control:	No
Colour of light according to EN 12464-1:	Warm white <3300 K	Photobiological safety according to EN 62471:	RG1
Socket:	Other	Compatible with Apple HomeKit:	No
Colour:	White	Compatible with Google Assistant:	No
Colour temperature:	3000 ~ 3000 K	Compatible with Amazon Alexa:	No
Housing colour:	Grey	IFTTT support available:	No
Beam angle:	24 ~ 24 °		

Packaging data

Weight	0.12 kg
Customs code	85395100

