

Satellite wall lamp basis E27 gold DIM



Satellite wall lamp basis E27 gold DIM	
Article number:	590025.00A
Status product:	126 - CURRENT
Changed last:	16-04-2025
Brand:	Daylight Italia
Type:	wall lamp satellite base
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC002892 - Ceiling-/wall luminaire
Synonym:	Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire



Feature

Suitable for wall mounting:	Yes	Rated life time L70/B50 at 25 °C:	0 h
Suitable for suspended mounting:	No	Rated life time L80/B10 at 25 °C:	0 h
Suitable for ceiling mounting:	No	Rated life time L90/B10 at 25 °C:	0 h
Suitable for built-in mounting:	No	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for surface mounting:	Yes	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for light line configuration:	No	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for workplace according to EN 12464-1:	No	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Lamp type:	LED exchangeable	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With light source:	No	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for number of light sources:	1	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
Lamp holder:	E27	Rated ambient temperature according to IEC 62722-2-1:	NA °C
Housing colour:	Gold	Suitable for emergency lighting:	No
Type of grid:	None	Emergency power supply integrated:	No
Nominal voltage:	220 ~ 240 V	With movement sensor:	No
Nominal current:	NA mA	With light sensor:	No
Type of control gear:	Not required	Covering of the luminaire with thermally insulating material possible:	No
With control gear:	No	With air slots:	No
Exchangeable control gear:	No	Suitable for lamp power:	NA W
Dimming 0-10 V:	No	Max. system power:	0 W
Dimming 1-10 V:	No	Luminaire efficacy:	0 lm/W
Dimming DALI-2:	No	Rated luminous flux according to IEC 62722-2-1:	0 lm
Dimming DALI:	No	Colour temperature:	NA K
Dimming DMX:	No	Constant light output (CLO):	No
Dimming DSI:	No	Width:	0 mm
Dimming potentiometer (integrated):	No	Height/depth:	0 mm
Dimming GPRS:	No	Length:	0 mm
Dimming LineSwitch:	No	Outer diameter:	0 mm
Dimming manufacturer's proprietary system:	No	Built-in length:	0 mm
Dimming mains voltage modulation:	No	Built-in width:	0 mm
Dimming phase cut-off:	No	Built-in height/depth:	0 mm
Dimming phase cut-on:	No	Built-in diameter:	0 mm
Dimming programmable:	No	Type of wiring:	Suitable for through wiring
Dimming RF:	No	Conductor cross section:	0 mm²
Dimming Sine Wave Reduction:	No	Luminous intensity:	0 cd
Dimming Touch and Dim:	No	Operation by Bluetooth:	No
Dimming Zigbee:	No	Compatible with Apple HomeKit:	No
Dimming with push-button:	No	Compatible with Google Assistant:	No
Dimming depending on control gear:	No	Compatible with Amazon Alexa:	No
No dim function:	No	IFTTT support available:	No

Packaging data

Weight	0 gr
Customs code	94051041

