

Satellite wall lamp basis E27 white DIM



| | |
|---|--|
| Satellite wall lamp basis E27 white DIM | |
| Article number: | 590028.00A |
| Status product: | 126 - CURRENT |
| Changed last: | 16-04-2025 |
| Brand: | Daylight Italia |
| Type: | wall lamp satellite base |
| ETIM Group: | EG000027 - Luminaires |
| ETIM Classes: | EC002892 - Ceiling-/wall luminaire |
| Synonym: | Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire |



Feature

| | | | |
|---|------------------|--|-----------------------------|
| Suitable for wall mounting: | Yes | Rated life time L70/B50 at 25 °C: | 0 h |
| Suitable for suspended mounting: | No | Rated life time L80/B10 at 25 °C: | 0 h |
| Suitable for ceiling mounting: | No | Rated life time L90/B10 at 25 °C: | 0 h |
| Suitable for built-in mounting: | No | Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for surface mounting: | Yes | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for light line configuration: | No | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for workplace according to EN 12464-1: | No | Failure rate at median useful life of 35,000 h at 25 °C ambient (tq): | 0 % |
| Lamp type: | LED exchangeable | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| With light source: | No | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq): | 0 % |
| Suitable for number of light sources: | 1 | Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | No |
| Lamp holder: | E27 | Rated ambient temperature according to IEC 62722-2-1: | 0 ~ 0 °C |
| Housing colour: | White | Suitable for emergency lighting: | No |
| Type of grid: | None | Emergency power supply integrated: | No |
| Nominal voltage: | 220 ~ 240 V | With movement sensor: | No |
| Nominal current: | 0 ~ 0 mA | With light sensor: | No |
| Type of control gear: | Not required | Covering of the luminaire with thermally insulating material possible: | No |
| With control gear: | No | With air slots: | No |
| Exchangeable control gear: | No | Suitable for lamp power: | 0 ~ 0 W |
| Dimming 0-10 V: | No | Max. system power: | 0 W |
| Dimming 1-10 V: | No | Luminaire efficacy: | 0 lm/W |
| Dimming DALI-2: | No | Rated luminous flux according to IEC 62722-2-1: | 0 lm |
| Dimming DALI: | No | Colour temperature: | 0 ~ 0 K |
| Dimming DMX: | No | Constant light output (CLO): | No |
| Dimming DSI: | No | Width: | 0 mm |
| Dimming potentiometer (integrated): | No | Height/depth: | 0 mm |
| Dimming GPRS: | No | Length: | 0 mm |
| Dimming LineSwitch: | No | Outer diameter: | 0 mm |
| Dimming manufacturer's proprietary system: | No | Built-in length: | 0 mm |
| Dimming mains voltage modulation: | No | Built-in width: | 0 mm |
| Dimming phase cut-off: | No | Built-in height/depth: | 0 mm |
| Dimming phase cut-on: | No | Built-in diameter: | 0 mm |
| Dimming programmable: | No | Type of wiring: | Suitable for through wiring |
| Dimming RF: | No | Conductor cross section: | 0 mm² |
| Dimming Sine Wave Reduction: | No | Luminous intensity: | 0 cd |
| Dimming Touch and Dim: | No | Operation by Bluetooth: | No |
| Dimming Zigbee: | No | Compatible with Apple HomeKit: | No |
| Dimming with push-button: | No | Compatible with Google Assistant: | No |
| Dimming depending on control gear: | No | Compatible with Amazon Alexa: | No |
| No dim function: | No | IFTTT support available: | No |

Packaging data

| | |
|--------------|----------|
| Weight | 0 gr |
| Customs code | 94051041 |

