

Led Downlight Jolly S round D85x59 CO75mm Black-Black GU10 LH



Led Downlight Jolly S round D85x59 CO75mm Black-Black GU10 LH	
Article number:	570139.00A
Status product:	126 - CURRENT
Changed last:	23-05-2025
Brand:	Daylight Italia
Type:	Round Fixture + GU10 Lamp Holder
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC001744 - Downlight/spot/floodlight
Synonym:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight




Feature

Suitable for surface mounting:	No	Dimming Zigbee:	No
Suitable for built-in mounting:	Yes	Dimming with push-button:	No
Suitable for wall mounting:	Yes	No dim function:	No
Suitable for suspended mounting:	No	Reflector:	Matt
Suitable for ceiling mounting:	Yes	Light distributor:	None
Suitable for traverse mounting:	No	Light sharing:	Symmetric
Suitable for pedestal/floor mounting:	No	Light outlet:	Direct
Suitable for light-track mounting:	No	Rated life time L70/B50 at 25 °C:	0 h
Suitable for clamp-mounting:	No	Rated life time L80/B10 at 25 °C:	0 h
Suitable for low voltage cable system:	No	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Adjustability:	Not adjustable	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With movement sensor:	No	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
With light sensor:	No	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Lamp type:	LED exchangeable	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With light source:	No	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
Suitable for number of light sources:	1	Constant light output (CLO):	No
Lamp holder:	GU10	Degree of protection (IP):	IP20
Housing material:	Aluminium	Rated ambient temperature according to IEC 62722-2-1:	0 ~ 0 °C
Surface protection:	Lacquered	Suitable for lamp power:	0 ~ 0 W
Housing colour:	Black	Max. system power:	50 W
Material cover:	None	Colour of light:	White
Surface brushed:	Yes	Colour temperature:	0 ~ 0 K
Nominal voltage:	220 ~ 240 V	Luminous flux:	0 ~ 0 lm
LED nominal current at constant current:	0 ~ 0 mA	Rated luminous flux according to IEC 62722-2-1:	0 lm
With control gear:	Yes	Luminous intensity:	0 cd
Exchangeable control gear:	No	Width:	85 mm
Dimming depending on control gear:	No	Height/depth:	32 mm
Dimming 0-10 V:	No	Length:	85 mm
Dimming 1-10 V:	No	Outer diameter:	85 mm
Dimming DALI-2:	No	Built-in width:	75 mm
Dimming DALI:	No	Built-in height/depth:	32 mm
Dimming DMX:	No	Built-in length:	75 mm
Dimming DSI:	No	Built-in diameter:	75 ~ 75 mm
Dimming potentiometer (integrated):	No	Conductor cross section:	0 mm²
Dimming GPRS:	No	Connectable conductor cross section:	0 ~ 0 mm²
Dimming LineSwitch:	No	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
Dimming manufacturer's proprietary system:	No	Emergency power supply integrated:	No
Dimming mains voltage modulation:	No	Luminaire efficacy:	0 lm/W
Dimming phase cut-off:	No	Suitable for workplace according to EN 12464-1:	No
Dimming phase cut-on:	No	Covering of the luminaire with thermally insulating material possible:	No
Dimming programmable:	No	IFTTT support available:	No
Dimming RF:	No	Compatible with Apple HomeKit:	No
Dimming Sine Wave Reduction:	No	Compatible with Google Assistant:	No
Dimming Touch and Dim:	No	Compatible with Amazon Alexa:	No

Packaging data

Weight	0 gr
Customs code	85389099



Included