

Elba pendel kit ball black + rosette black + 1,5m black cable



Elba pendel kit ball black + rosette black + 1,5m black cable	
Article number:	800020.00A
Status product:	126 - CURRENT
Changed last:	13-03-2025
Brand:	Daylight Italia
Type:	Elba pendel kit
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC001743 - Pendant luminaire
Synonym:	Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire



Feature

Suitable for light line configuration:	No	Dimming with push-button:	No
Suitable for workplace according to EN 12464-1:	No	No dim function:	No
Lamp type:	LED exchangeable	Light distributor:	None
With light source:	No	Reflector:	None
Suitable for number of light sources:	1	Direct-/indirect proportion separately controllable:	No
Lamp holder:	E27	Rated life time L70/B50 at 25 °C:	0 h
Housing material:	Plastic	Rated life time L80/B10 at 25 °C:	0 h
Housing colour:	Black	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Material cover:	Plastic, opal	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Type of grid:	High-gloss	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Nominal voltage:	220 ~ 240 V	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Nominal current:	0 ~ 0 mA	Degree of protection (IP):	IP20
LED nominal current at constant current:	0 ~ 0 mA	Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24:	No
Type of control gear:	Not required	Suitable for emergency lighting:	No
With control gear:	No	Emergency power supply integrated:	No
Exchangeable control gear:	No	Suitable for lamp power:	0 ~ 0 W
Dimming 0-10 V:	No	Max. system power:	0 W
Dimming 1-10 V:	No	Rated luminous flux according to IEC 62722-2-1:	0 lm
Dimming DALI:	No	Luminaire efficacy:	0 lm/W
Dimming DALI-2:	No	Colour temperature:	0 ~ 0 K
Dimming DMX:	No	Constant light output (CLO):	No
Dimming programmable:	No	Width:	80 mm
Dimming DSI:	No	Height/depth:	80 mm
Dimming RF:	No	Length:	1500 mm
Dimming potentiometer (integrated):	No	Diameter:	80 mm
Dimming GPRS:	No	With suspension:	Yes
Dimming LineSwitch:	No	Pendant length:	1500 ~ 1500 mm
Dimming manufacturer's proprietary system:	No	Conductor cross section:	0 mm²
Dimming mains voltage modulation:	No	Connection type:	Push-in clamp
Dimming phase cut-off:	No	Compatible with Apple HomeKit:	No
Dimming phase cut-on:	No	Compatible with Google Assistant:	No
Dimming Sine Wave Reduction:	No	Compatible with Amazon Alexa:	No
Dimming Touch and Dim:	No	IFTTT support available:	No
Dimming Zigbee:	No		

Packaging data

Weight	0 gr
Customs code	85444290

