

## Kit pendel 2x cilinder chrome + white cable Bellaluce



Kit pendel 2x cilinder chrome + white cable Bellaluce

|                 |   |
|-----------------|---|
| Article number: | 810065.00A  |
| Status product: | 126 - CURRENT   |
| Changed last:   | 13-03-2025  |
| Brand:          | Daylight Italia   |
| Type:           | Kit pendel  |
| ETIM Group:     | EG000027 - Luminaires   |
| ETIM Classes:   | EC001743 - Pendant luminaire  |
| Synonym:        | Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire |



## Feature

|   |                  |  |                       |
|---|------------------|--|-----------------------|
| Suitable for light line configuration:          | No               | Light outlet:  | Direct                |
| Suitable for workplace according to EN 12464-1: | No               | Direct-/indirect proportion separately controllable:                             | No                    |
| Lamp type:                                      | LED exchangeable | Energy efficiency class of the built-in lamp:                                    | Other                 |
| With light source:                              | Yes              | Energy efficiency class of the provided exchangeable built-in lamp:              | E                     |
| Suitable for number of light sources:           | 2                | Highest energy efficiency class of the exchangeable lamp:                        | E                     |
| Lamp holder:                                    | E27              | Lowest energy efficiency class of the exchangeable lamp:                         | E                     |
| Housing material:                               | Plastic          | Rated life time L70/B50 at 25 °C:  | 15000 h               |
| Housing colour:                                 | White            | Rated life time L80/B10 at 25 °C:  | 15000 h               |
| Material cover:                                 | Plastic, opal    | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):       | 0 %                   |
| Type of grid:                                   | White            | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):       | 0 %                   |
| Nominal voltage:                                | 220 ~ 240 V      | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):            | 0 %                   |
| Nominal current:                                | 0 ~ 0 mA         | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):            | 0 %                   |
| LED nominal current at constant current:        | 0 ~ 0 mA         | Degree of protection (IP):   | IP20                  |
| Type of control gear:                           | Not required     | Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | No                    |
| With control gear:                              | No               | Suitable for emergency lighting:   | No                    |
| Exchangeable control gear:                      | No               | Emergency power supply integrated:   | No                    |
| Dimming 0-10 V:                                 | No               | Filament test according to IEC 60695-2-11:                                       | None                  |
| Dimming 1-10 V:                                 | No               | Suitable for lamp power:   | 0 ~ 0 W               |
| Dimming DALI:                                   | No               | Max. system power:   | 0 W                   |
| Dimming DALI-2:                                 | No               | Rated luminous flux according to IEC 62722-2-1:                                  | 2000 lm               |
| Dimming DMX:                                    | No               | Colour of light:   | White                 |
| Dimming programmable:                           | No               | Luminaire efficacy:  | 100 lm/W              |
| Dimming DSI:                                    | No               | Colour temperature:  | 2700 ~ 2700 K         |
| Dimming RF:                                     | No               | Colour rendering index CRI:  | 80-89                 |
| Dimming potentiometer (integrated):             | No               | Constant light output (CLO):   | No                    |
| Dimming GPRS:                                   | No               | Colour of light adjustable:  | No                    |
| Dimming LineSwitch:                             | No               | Luminous flux adjustable:  | Continuously variable |
| Dimming manufacturer's proprietary system:      | No               | Beam angle adjustable:   | No                    |
| Dimming mains voltage modulation:               | No               | Width:   | 120 mm                |
| Dimming phase cut-off:                          | Yes              | Height/depth:  | 1500 mm               |
| Dimming phase cut-on:                           | No               | Length:  | 120 mm                |
| Dimming Sine Wave Reduction:                    | No               | Diameter:  | 120 mm                |
| Dimming Touch and Dim:                          | No               | With suspension:   | Yes                   |
| Dimming Zigbee:                                 | No               | Pendant length:  | 1500 ~ 1500 mm        |
| Dimming with push-button:                       | No               | Conductor cross section:   | 0 mm²                 |
| No dim function:                                | No               | Compatible with Apple HomeKit:   | No                    |
| Light distributor:                              | None             | Compatible with Google Assistant:  | No                    |
| Reflector:                                      | None             | Compatible with Amazon Alexa:  | No                    |
| Light sharing:                                  | Symmetric        | IFTTT support available:   | No                    |

## Packaging data

---

|              |          |
|--------------|----------|
| Weight       | 0 gr     |
| Customs code | 94051041 |

---

