

Kit cluster 5x Cri white + white cable G125 Opal



Kit cluster 5x Cri white + white cable G125 Opal

| | |
|-----------------|---|
| Article number: | 810066.00A |
| Status product: | 126 - CURRENT |
| Changed last: | 13-03-2025 |
| Brand: | Daylight Italia |
| Type: | Kit cluster |
| ETIM Group: | EG000027 - Luminaires |
| ETIM Classes: | EC001743 - Pendant luminaire |
| Synonym: | Grid luminaire, Pendant luminaire, Prisms luminaire, Watertight luminaire |



Feature

| | | | |
|--|------------------|--|----------------|
| Suitable for light line configuration: | No | Energy efficiency class of the built-in lamp: | Other |
| Suitable for workplace according to EN 12464-1: | No | Energy efficiency class of the provided exchangeable built-in lamp: | E |
| Lamp type: | LED exchangeable | Highest energy efficiency class of the exchangeable lamp: | E |
| With light source: | Yes | Lowest energy efficiency class of the exchangeable lamp: | E |
| Suitable for number of light sources: | 5 | Rated life time L70/B50 at 25 °C: | 15000 h |
| Lamp holder: | E27 | Rated life time L80/B10 at 25 °C: | 15000 h |
| Housing material: | Plastic | Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Housing colour: | White | Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq): | 0 % |
| Material cover: | Plastic, opal | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
| Type of grid: | White | Failure rate at median useful life of 75,000 h at 25 °C ambient (tq): | 0 % |
| Nominal voltage: | 220 ~ 240 V | Degree of protection (IP): | IP20 |
| Nominal current: | 0 ~ 0 mA | Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: | No |
| LED nominal current at constant current: | 0 ~ 0 mA | Suitable for emergency lighting: | No |
| Type of control gear: | Not required | Emergency power supply integrated: | No |
| With control gear: | No | Filament test according to IEC 60695-2-11: | None |
| Exchangeable control gear: | No | Suitable for lamp power: | 0 ~ 0 W |
| Dimming 0-10 V: | No | Max. system power: | 0 W |
| Dimming 1-10 V: | No | Rated luminous flux according to IEC 62722-2-1: | 20150 lm |
| Dimming DALI: | No | Colour of light: | White |
| Dimming DALI-2: | No | Luminaire efficacy: | 537.3 lm/W |
| Dimming DMX: | No | Colour temperature: | 2700 ~ 2700 K |
| Dimming programmable: | No | Colour rendering index CRI: | 80-89 |
| Dimming DSI: | No | Constant light output (CLO): | No |
| Dimming RF: | No | Colour of light adjustable: | No |
| Dimming potentiometer (integrated): | No | Luminous flux adjustable: | No |
| Dimming GPRS: | No | Beam angle adjustable: | No |
| Dimming LineSwitch: | No | Width: | 120 mm |
| Dimming manufacturer's proprietary system: | No | Height/depth: | 120 mm |
| Dimming mains voltage modulation: | No | Length: | 1500 mm |
| Dimming phase cut-off: | Yes | Diameter: | 120 mm |
| Dimming phase cut-on: | No | With suspension: | Yes |
| Dimming Sine Wave Reduction: | No | Pendant length: | 1500 ~ 1500 mm |
| Dimming Touch and Dim: | No | Type of wiring: | Ending |
| Dimming Zigbee: | No | Number of poles: | 2 |
| Dimming with push-button: | No | Conductor cross section: | 0 mm² |
| No dim function: | No | Connection type: | Push-in clamp |
| Light distributor: | None | Compatible with Apple HomeKit: | No |
| Reflector: | None | Compatible with Google Assistant: | No |
| Light sharing: | Symmetric | Compatible with Amazon Alexa: | No |
| Light outlet: | Direct | IFTTT support available: | No |
| Direct-/indirect proportion separately controllable: | No | | |

Packaging data

| | |
|--------------|----------|
| Weight | 0 gr |
| Customs code | 94051041 |

